

# COMPUTING

## ATCA-F140

Control via IPMI Programmer's Reference

P/N: 6806800R08F

December 2017

**ARTESYN**<sup>™</sup>  
EMBEDDED TECHNOLOGIES

© Copyright 2017 Artesyn Embedded Technologies, Inc.  
All rights reserved.

## Trademarks

Artesyn Embedded Technologies, Artesyn and the Artesyn Embedded Technologies logo are trademarks and service marks of Artesyn Embedded Technologies, Inc. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners. © 2017 Artesyn Embedded Technologies, Inc. All rights reserved. For full legal terms and conditions, please visit [www.artesyn.com/legal](http://www.artesyn.com/legal).

## Notice

While reasonable efforts have been made to assure the accuracy of this document, Artesyn assumes no liability resulting from any omissions in this document, or from the use of the information obtained therein. Artesyn reserves the right to revise this document and to make changes from time to time in the content hereof without obligation of Artesyn to notify any person of such revision or changes.

Electronic versions of this material may be read online, downloaded for personal use, or referenced in another document as a URL to an Artesyn website. The text itself may not be published commercially in print or electronic form, edited, translated, or otherwise altered without the permission of Artesyn.

It is possible that this publication may contain reference to or information about Artesyn products (machines and programs), programming, or services that are not available in your country. Such references or information must not be construed to mean that Artesyn intends to announce such Artesyn products, programming, or services in your country.

## Limited and Restricted Rights Legend

If the documentation contained herein is supplied, directly or indirectly, to the U.S. Government, the following notice shall apply unless otherwise agreed to in writing by Artesyn.

Use, duplication, or disclosure by the Government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data clause at DFARS 252.227-7013 (Nov. 1995) and of the Rights in Noncommercial Computer Software and Documentation clause at DFARS 252.227-7014 (Jun. 1995).

## Contact Address

Artesyn Embedded Technologies  
Marketing Communications  
2900 S. Diablo Way, Suite 190  
Tempe, Arizona 85282

# Contents

<b>About this Manual</b> .....	<b>7</b>
<b>1 Introduction</b> .....	<b>11</b>
1.1 Features .....	11
<b>2 Supported IPMI Commands</b> .....	<b>13</b>
2.1 Introduction .....	13
2.2 Standard IPMI Commands .....	13
2.2.1 Global IPMI Commands .....	13
2.2.2 BMC Device and Messaging Commands .....	14
2.2.3 BMC WatchDog Timer Commands .....	14
2.2.4 Chassis Device Commands .....	15
2.2.5 Event Commands .....	15
2.2.6 Sensor Device Commands .....	16
2.2.7 FRU Inventory Commands .....	16
2.2.8 SEL Device Commands .....	17
2.2.9 Serial/Modem Device Commands .....	17
2.3 PICMG 3.0 Commands .....	18
2.4 PICMG AMC.0 Commands .....	19
2.5 Firmware Upgrade Commands .....	19
2.6 Artesyn OEM Commands .....	20
2.6.1 Set Feature Configuration (NetFn = 0x2E/0x2F, CMD = 0x1E) .....	21
2.6.2 Get Feature Configuration (NetFn = 0x2E/0x2F, CMD = 0x1F) .....	24
2.6.3 Get Payload Upgrade Flag (NetFn = 0x30/0x31, CMD = 0xE2) .....	25
2.6.4 Set Payload Upgrade Flag (NetFn = 0x30/0x31, CMD = 0xE3) .....	25
2.6.5 Get Boot Bank Swap Control (NetFn = 0x30/0x31, CMD = 0xE4) .....	26
2.6.6 Set Boot Bank Swap Control (NetFn = 0x30/0x31, CMD = 0xE5) .....	26
<b>3 FRU Information and Sensor Data Records</b> .....	<b>27</b>
3.1 FRU Data .....	27
3.2 MAC Address Record .....	34
3.3 Power Configuration .....	35
3.4 Sensor Overview .....	36

<b>4</b>	<b>OEM Sensors</b> .....	<b>73</b>
4.1	OEM Sensors .....	73
<b>A</b>	<b>Related Documentation</b> .....	<b>75</b>
A.1	Artesyn Embedded Technologies - Embedded Computing Documentation .....	75
A.2	Related Specifications .....	75

# List of Tables

Table 2-1	Supported Global IPMI Commands	13
Table 2-2	BMC Device and Messaging Commands	14
Table 2-3	Supported BMC WatchDog Timer Commands	14
Table 2-4	Supported Chassis Device Commands	15
Table 2-5	Supported Event Commands	15
Table 2-6	Supported Sensor Device Commands	16
Table 2-7	Supported FRU Commands	16
Table 2-8	Supported SEL Commands	17
Table 2-9	Supported Serial/Modem Device Commands	17
Table 2-10	Supported PICMG 3.0 Commands	18
Table 2-11	PICMG AMC.0 Commands	19
Table 2-12	Firmware Upgrade Commands	19
Table 2-13	Artesyn OEM Commands	20
Table 2-14	Set Feature Configuration	21
Table 2-15	Feature Selector Assignments	23
Table 2-16	Get Feature Configuration Command	24
Table 2-17	Get Payload Upgrade Flag	25
Table 2-18	Set Payload Upgrade Flag Command	25
Table 2-19	Get Boot Bank Swap Control Command	26
Table 2-20	Set Boot Bank Swap Control Command	26
Table 3-1	Artesyn MAC Addresses Record	34
Table 3-2	Artesyn MAC Address Descriptor	35
Table 3-3	Interface Type Assignments	35
Table 3-4	IPMI Sensors Overview	36
Table 3-5	Hot Swap Carrier	38
Table 3-6	ATCA-F140 HS RTM	38
Table 3-7	Hotswap AMC 5	39
Table 3-8	Version change	40
Table 3-9	IPMB Physical	40
Table 3-10	BMC Watchdog	41
Table 3-11	12.0V Sensor	42
Table 3-12	3.3V Sensor	43
Table 3-13	1.0V FIX VDDC	44
Table 3-14	1.0V FIX VDDC	45
Table 3-15	1.0V FIX AVDD	46
Table 3-16	1.5V	47

Table 3-17	1.2V BIX .....	48
Table 3-18	1.05V .....	49
Table 3-19	1.0V .....	50
Table 3-20	Inlet Temp .....	51
Table 3-21	BIX Temp .....	51
Table 3-22	FIX Temp .....	52
Table 3-23	SP Temp .....	53
Table 3-24	Clock Temp .....	54
Table 3-25	RTM Top Temp .....	55
Table 3-26	RTM Mid Temp .....	56
Table 3-27	RTM Bottom Temp .....	57
Table 3-28	IPMC POST .....	58
Table 3-29	Boot Bank .....	59
Table 3-30	Reserved .....	60
Table 3-31	Fw Progress .....	60
Table 3-32	OS Boot .....	61
Table 3-33	Boot Error .....	62
Table 3-34	Boot Initiated .....	62
Table 3-35	ATCA-F140 IPMC .....	63
Table 3-36	Power Good .....	64
Table 3-37	-48V A Volts .....	64
Table 3-38	-48V B Volts .....	65
Table 3-39	-48V Amps .....	66
Table 3-40	HoldUp Cap Volts .....	67
Table 3-41	iQor Temp .....	68
Table 3-42	iQor Status .....	69
Table 3-43	Reset Source .....	70
Table 3-44	POST Code .....	71
Table 3-45	RTM Power Good .....	71
Table 4-1	OEM Sensor .....	73
Table A-1	Artesyn Embedded Technologies - Embedded Computing Publications .....	75
Table A-2	Related Specifications .....	75

# About this Manual

## Overview of Contents

This manual provides information on how to control and monitor the functionality of the ATCA-F140 via Intelligent Platform Management Interface (IPMI).

This manual is intended for users qualified in software development. Users must have a working understanding of IPMI.

This manual is divided into the following chapters and appendices.

[Chapter 1, \*Introduction\*](#) gives a short overview on the ATCA-F140.

[Chapter 2, \*Supported IPMI Commands\*](#), lists IPMI commands supported by the IPMC.

[Chapter 3, \*FRU Information and Sensor Data Records\*](#), provides FRU information and sensors that are accessible via IPMI for ATCA-F140.

[Chapter 4, \*OEM Sensors\*](#), provides additional information about OEM sensors that are accessible via IPMI for ATCA-F140.

[Appendix A, \*Related Documentation\*](#), lists publications for blade and software products used with the ATCA-F140 platforms.

## Abbreviations

This document uses the following terms and abbreviations:

Term	Definition
FRU	Field Replaceable Unit. A module or component which will typically be replaced in its entirety as part of a field service repair operation.
FTM	Fan Tray Module. An FRU that provides cooling to the shelf.
IPMB	Intelligent Platform Management Bus. Name for the architecture, protocol, and implementation of a special bus that interconnects the baseboard and chassis electronics and provides a communications media for system platform management information. The bus is built on I <sup>2</sup> C and provides a communications path between “management controllers” such as the BMC, FPC, and HSC.
LPMI	Local Peripheral Manager Interface.





Term	Definition
LUN	Logical Unit Number. In the context of the Intelligent Platform Management Bus protocol, this is a subaddress that allows messages to be routed to different 'logical units' that reside behind the same I <sup>2</sup> C slave address.
PEM	Power Entry Module. An FRU that introduces power to the shelf.
SAM	Shelf Manager. An FRU that provides system management functions for shelf components.
SDR	Sensor Data Record. A data record that provides platform management sensor type, locations, event generation, and access information.
SEL	System Event Log. A non-volatile storage area and associated interfaces for storing system platform event information for later retrieval.

## Conventions

The following table describes the conventions used throughout this manual.

Notation	Description
0x00000000	Typical notation for hexadecimal numbers (digits are 0 through F), for example used for addresses and offsets
0b0000	Same for binary numbers (digits are 0 and 1)
<b>bold</b>	Used to emphasize a word
Screen	Used for on-screen output and code related elements or commands in body text
<b>Courier + Bold</b>	Used to characterize user input and to separate it from system output
<i>Reference</i>	Used for references and for table and figure descriptions
File > Exit	Notation for selecting a submenu
<text>	Notation for variables and keys
[text]	Notation for software buttons to click on the screen and parameter description
...	Repeated item for example node 1, node 2, ..., node 12



Notation	Description
<p>. . .</p>	<p>Omission of information from example/command that is not necessary at the time being</p>
<p>..</p>	<p>Ranges, for example: 0..4 means one of the integers 0,1,2,3, and 4 (used in registers)</p>
<p> </p>	<p>Logical OR</p>
	<p>Indicates a hazardous situation which, if not avoided, could result in death or serious injury</p>
	<p>Indicates a hazardous situation which, if not avoided, may result in minor or moderate injury</p>
	<p>Indicates a property damage message</p>
	<p>No danger encountered. Pay attention to important information</p>

## Summary of Changes

See the table below for manual revisions and changes.

Part Number	Date	Description
6806800R08F	December, 2017	Updated copyrights page.
6806800R08E	June, 2016	Re-branded to new template.
6806800R08D	April, 2015	Updated <i>Appendix A, Related Documentation on page 75.</i>
6806800R08C	March, 2014	Updated Chapter 2, Supported IPMI Commands, and Re-branded to Artestyn template.
6806800R08B	November, 2013	Updated <i>Chapter 3, Sensor Overview</i> and <i>Chapter A, Emerson Network Power - Embedded Computing Documents.</i>
6806800R08A	February, 2013	First Version

## 1.1 Features

The ATCA-F140 is a hub board as defined in *PICMG 3.0 Revision 3.0 Advanced TCA Base Specification* and *PICMG 3.1 Revision 1.0 Specification Ethernet/Fiber Channel for Advanced TCA Systems*. It supports several Base and Fabric Channel Ethernet interfaces to the Zone 2 backplane. It also supports 1Gb, 10Gb, and 40Gb Ethernet uplinks to the front panel and to a Rear Transition Module (RTM) through the Zone 3 connector.

Broadcom Ethernet switches and PHYs are used for the base and fabric channels. The entire board is managed by a Freescale P2020 QorIQ Integrated Processor.

The ATCA-F140 provides one AMC bay. This bay is designed to support a processor AMC module for additional applications processing capabilities on the board.

See the list below for the key features of the ATCA-F140:

- Single slot ATCA form factor (280 mm x 322 mm)
- Freescale P2020 QorIQ Integrated Processor for the on board service processor functions
- Two DDR3 memory DIMM slots; each of which can support up to 2 GB of DDR3 SDRAM with ECC for a total memory capacity of 4 GB
- Two redundant banks of 32 MB Boot Flash memory
- 2 GB embedded USB Flash module for User Flash memory
- Onboard SATA connector for a 2.5" SATA drive with selectable interface to either the service processor or the processor AMC
- Real time clock
- RJ-45 UART Console interface to service processor on front panel
- RJ-45 10/100/1000 BaseTx Ethernet Management port on the front panel for P2020 QorIQ Integrated Processor
- Broadcom BCM56334 managed switch device for the Base Channel (24 1G-SGMII and four 10G-XAUI ports)
- Two Fabric Channel 40G (QSFP+) uplink ports on the front panel
- Multiple 1 GbE SGMII and 10 GbE XAUI ports routed to Zone 3 connectors for base and fabric uplink channels on RTM
- Two 40G ports routed to Zone 3 connectors for fabric uplink on RTM

- Stratum 3 Telco clock option with master/slave sync and 5 inter-shelf sync connectors on front panel along with 2 BITS/SSU front panel connectors
- Synchronous Ethernet support
- One AMC bay for application processor support
- IPMC functionality for the board management by the Shelf Management Controller

# Supported IPMI Commands

## 2.1 Introduction

This chapter describes the different commands supported by the ATCA-F140 series platforms. Command categories are as follows:

- *Standard IPMI Commands*
- *PICMG 3.0 Commands*
- *PICMG AMC.0 Commands*
- *Firmware Upgrade Commands*
- *Artesyn OEM Commands*

## 2.2 Standard IPMI Commands

The IPMC is fully compliant to the Intelligent Platform Management Interface v.1.5. This section provides information about the supported IPMI commands.

### 2.2.1 Global IPMI Commands

The IPMCs support the following global IPMI commands.

*Table 2-1 Supported Global IPMI Commands*

Command Name	NetFn	CMD
Get Device ID	App	01h
Cold Reset	App	02h
Warm Reset	App	03h
Get Self Test Results	App	04h
Get Device GUID	App	08h
Broadcast "Get Device ID"	APP	01h

## 2.2.2 BMC Device and Messaging Commands

The IPMCs support the following BMC Device and Messaging Timer commands.

*Table 2-2 BMC Device and Messaging Commands*

Command Name	NetFn	CMD
Set BMC Global Enables	App	2Eh
Get BMC Global Enables	App	2Fh
Clear Message Flags	App	30h
Get Message Flags	App	31h
Get Message	App	33h
Send Message	App	34h
Master Write-Read	App	52h
Get Channel Info	App	42h

## 2.2.3 BMC WatchDog Timer Commands

The IPMCs support the following BMC WatchDog Timer commands.

*Table 2-3 Supported BMC WatchDog Timer Commands*

Command Name	NetFn	CMD
Reset Watchdog Timer	App	22h
Set Watchdog Timer	App	24h
Get Watchdog Timer	App	25h

## 2.2.4 Chassis Device Commands

The IPMC supports the following chassis device commands.

*Table 2-4 Supported Chassis Device Commands*

Command Name	NetFn	CMD
Set System Boot Options	Chassis	08h
Get System Boot Options	Chassis	09h



These commands are supported only by certain OEM boot options. The standard boot options are not supported.

## 2.2.5 Event Commands

The IPMC supports the following event commands.

*Table 2-5 Supported Event Commands*

Command Name	NetFn	CMD
Set Event Receiver	S/E	00h
Get Event Receiver	S/E	01h
Platform Event (a.k.a. "Event Message")	S/E	02h

## 2.2.6 Sensor Device Commands

The IPMCs support the following sensor device commands.

*Table 2-6 Supported Sensor Device Commands*

Command Name	NetFn	CMD
Get Device SDR Info	S/E	20h
Get Device SDR	S/E	21h
Reserve Device SDR Repository	S/E	22h
Set Sensor Hysteresis	S/E	24h
Get Sensor Hysteresis	S/E	25h
Set Sensor Threshold	S/E	26h
Get Sensor Threshold	S/E	27h
Set Sensor Event Enable	S/E	28h
Get Sensor Event Enable	S/E	29h
Get Sensor Event Status	S/E	2Bh
Get Sensor Reading	S/E	2Dh
Get Sensor Type	S/E	2Fh

## 2.2.7 FRU Inventory Commands

The IPMCs support the following FRU inventory commands.

*Table 2-7 Supported FRU Commands*

Command Name	NetFn	CMD
Get FRU Inventory Area Info	Storage	10h
Read FRU Data	Storage	11h



*Table 2-7 Supported FRU Commands*

Command Name	NetFn	CMD
Write FRU Data	Storage	12h

## 2.2.8 SEL Device Commands

The IPMC supports the following SEL device commands.

*Table 2-8 Supported SEL Commands*

Command Name	NetFn	CMD
Get SEL Info	Storage	40h
Reserve SEL	Storage	42h
Get SEL Entry	Storage	43h
Add SEL Entry	Storage	44h
Clear SEL	Storage	47h
Get SEL Time	Storage	48h
Set SEL Time	Storage	49h

## 2.2.9 Serial/Modem Device Commands

The IPMC supports the following serial/modem device commands.

*Table 2-9 Supported Serial/Modem Device Commands*

Command Name	NetFn	CMD
Set Serial/Modem Configuration	Transport	10h
Get Serial/Modem Configuration	Transport	11h

## 2.3 PICMG 3.0 Commands

The Artesyn IPMC is a fully compliant AdvancedTCA Intelligent Platform Management Controller. It supports all required and mandatory AdvancedTCA commands as defined in the PICMG 3.0 specification.

*Table 2-10 Supported PICMG 3.0 Commands*

Command Name	NetFn	CMD
Get PICMG Properties	PICMG	00h
Get Address Info	PICMG	01h
FRU Control	PICMG	04h
Get FRU LED Properties	PICMG	05h
Get LED Color Capabilities	PICMG	06h
Set FRU LED State	PICMG	07h
Get FRU LED State	PICMG	08h
Set IPMB State	PICMG	09h
Set FRU Activation Policy	PICMG	0Ah
Get FRU Activation Policy	PICMG	0Bh
Set FRU Activation	PICMG	0Ch
Get Device Locator Record ID	PICMG	0Dh
Set Port State	PICMG	0Eh
Get Port State	PICMG	0Fh
Compute Power Properties	PICMG	10h
Set Power Level	PICMG	11h
Get Power Level	PICMG	12h

*Table 2-10 Supported PICMG 3.0 Commands*

Command Name	NetFn	CMD
Bused Resource	PICMG	17h
Get IPMB Link Info	PICMG	18h
FRU Control Capabilities	PICMG	1Eh

## 2.4 PICMG AMC.0 Commands

Following are the PICMG AMC.0 commands. These commands are supported to comply with the PICMG AMC.0 specification as an AMC carrier.

*Table 2-11 PICMG AMC.0 Commands*

Command Name	NetFn	CMD
Set AMC Port State	PICMG	19h
Get AMC Port State	PICMG	1Ah

## 2.5 Firmware Upgrade Commands

Following are the firmware upgrade commands. These commands are to support the PICMG HPM.1 firmware upgrade protocol.

*Table 2-12 Firmware Upgrade Commands*

Command Name	NetFn	CMD
Get Target Upgrade Capabilities	PICMG	2Eh
Get Component Properties	PICMG	2Fh
Abort Firmware Upgrade	PICMG	30h
Initiate Upgrade Action	PICMG	31h
Upload Firmware Block	PICMG	32h
Finish Firmware Upload	PICMG	33h

Table 2-12 Firmware Upgrade Commands

Command Name	NetFn	CMD
Get Upgrade Status	PICMG	34h
Activate Firmware	PICMG	35h
Query Self-test Results	PICMG	36h
Query Rollback Status	PICMG	37h
Initiate Manual Rollback	PICMG	38h

## 2.6 Artesyn OEM Commands

The Artesyn IPMC supports several commands which are not defined in the IPMI or PICMG 3.0 specification but are introduced by Artesyn.

Table 2-13 Artesyn OEM Commands

Command Name	NetFn	CMD	Detailed Description
Set Feature Configuration	EMR	1Eh	See, <a href="#">Set Feature Configuration (NetFn = 0x2E/0x2F, CMD = 0x1E)</a>
Get Feature Configuration	EMR	1Fh	See, <a href="#">Get Feature Configuration (NetFn = 0x2E/0x2F, CMD = 0x1F)</a>
Get Upgrade Flag	OEM_0	E2h	See <a href="#">Get Payload Upgrade Flag (NetFn = 0x30/0x31, CMD = 0xE2)</a>
Set Upgrade Flag	OEM_0	E3h	See <a href="#">Set Payload Upgrade Flag (NetFn = 0x30/0x31, CMD = 0xE3)</a>
Get Swap Flag	OEM_0	E4h	See <a href="#">Get Boot Bank Swap Control (NetFn = 0x30/0x31, CMD = 0xE4)</a>
Set Swap Flag	OEM_0	E5h	See <a href="#">Set Boot Bank Swap Control (NetFn = 0x30/0x31, CMD = 0xE5)</a>

## 2.6.1 Set Feature Configuration (NetFn = 0x2E/0x2F, CMD = 0x1E)

This command can be used to enable/disable or configure features implemented on the blade at runtime.

*Table 2-14 Set Feature Configuration*

	Byte	Data Field
Request Data	1	LSB of Artesyn IANA Enterprise Number. A value of CDh shall be used.
	2	2nd byte of Artesyn IANA Enterprise Number. A value of 65h shall be used.
	3	MSB of Artesyn IANA Enterprise Number. A value of 00h shall be used.
	4	Feature Selector.E0h - FFh = product specific feature for details, please see <a href="#">Table 2-15 on page 23</a> .
	5	Feature Configuration. Please see <a href="#">Table 2-15 on page 23</a> .

Table 2-14 Set Feature Configuration

	Byte	Data Field
	(6)	<p>Persistency / Duration. Not all values are valid for a particular feature or product.</p> <p>00h = volatile.</p> <p>Actual duration depends on implementation.</p> <p>01h - FAh = duration in 100ms.</p> <p>Previous State is restored after expiration.</p> <p>FBh = not take effect until next cold reset or warm reset depending on implementation</p> <p>FCh = not take effect until next hard reset or power cycle</p> <p>FDh = till cold reset or warm reset depending on implementation</p> <p>FEh = till hard reset or power cycle</p> <p>FFh = persistent over power cycle (default)</p>
	(7)	<p>Feature Configuration Modifier.</p> <p>Omitted if not used or default to 00h. Refer to <a href="#">Table 2-15 on page 23</a></p>
Response Data	1	<p>Completion Code. Generic plus the following command-specific completion codes:</p> <p>80h = feature selector not supported.</p> <p>81h = feature configuration not supported</p> <p>82h = configuration persistency / duration not supported</p> <p>83h = feature configuration modifier not supported</p>
	2	<p>LSB of Artesyn IANA Enterprise Number. A value of CDh shall be used.</p>
	3	<p>2nd byte of Artesyn IANA Enterprise Number. A value of 65h shall be used.</p>
	4	<p>MSB of Artesyn IANA Enterprise Number. A value of 00h shall be used.</p>

Table 2-15 Feature Selector Assignments

Feature Selector	Description & Configuration Modifier	Configuration Modifier	Feature Configuration
2	System Status Manager	00h = System Status Manager	00h = disabled 01h = enabled 02h = restore factory default (including the max message interval and the max startup delay) 03h - FFh reserved
		01h = Monitor Central heartbeat interval timer (in 1 second)	00h = disabled. Timer setting not changed. 01h = enabled. Timer setting not changed. 02h = restore factory default timer setting 03h - FFh: timer value in 1 second (3 ~ 255 seconds)
		02h = Monitor Central startup delay timer (in 10 seconds)	00h = disabled. Timer setting not changed. 01h = enabled. Timer setting not changed. 02h = restore factory default timer setting 03h - FFh: timer value in 10 second (30 ~ 2550 seconds)
		03h - FFh: reserved	N/A
3	Handle Switch De-bounce	FRU Device ID. 00h = Front blade 01h = RTM 02h - FFh: reserved	00h = disabled (may not be valid, or implementation defined) 01h = enabled (may be ignored or implementation defined) 02h = restore factory default merge the two to be: 03h - FFh = De-bounce timer timeout value in 100ms.

## 2.6.2 Get Feature Configuration (NetFn = 0x2E/0x2F, CMD = 0x1F)

This command retrieves the configuration of the feature implemented on the blade.

*Table 2-16 Get Feature Configuration Command*

	Byte	Data Field
Request Data	1	LSB of Artesyn IANA Enterprise Number. A value of CDh shall be used.
	2	2nd byte of Artesyn IANA Enterprise Number. A value of 65h shall be used.
	3	MSB of Artesyn IANA Enterprise Number. A value of 00h shall be used.
	4	Feature Selector, for details see <a href="#">Table 2-15 on page 23</a> .
	(5)	Feature Configuration Modifier. Omitted if not used. For details see <a href="#">Table 2-15 on page 23</a> .
Response Data	1	Completion Code. Generic plus the following command-specific completion codes: 80h = feature selector not supported. 83h = feature configuration modifier not supported
	2	LSB of Artesyn IANA Enterprise Number. A value of CDh shall be used.
	3	2nd byte of Artesyn IANA Enterprise Number. A value of 65h shall be used.
	4	MSB of Artesyn IANA Enterprise Number. A value of 00h shall be used.
	5	Feature Configuration
	6	Persistency / Duration



### 2.6.3 Get Payload Upgrade Flag (NetFn = 0x30/0x31, CMD = 0xE2)

This command retrieves the Payload Upgrade Flag. When the Payload Upgrade Flag is set, it overrides the boot bank swap control setting, and force the boot bank swap feature to be enabled upon the BMC Watchdog Timer expiration.

*Table 2-17 Get Payload Upgrade Flag*

	Byte	Data Field
Request Data	-	-
Response Data	1	Completion Code.
	2	Upgrade Flag. 0 = Payload not in upgrade mode. 1 = Payload in upgrade mode. Boot bank will be swapped upon BMC Watchdog Timer expiration.

### 2.6.4 Set Payload Upgrade Flag (NetFn = 0x30/0x31, CMD = 0xE3)

This command sets the Payload Upgrade Flag. This command should be used only by the payload upgrade script or utilities.

*Table 2-18 Set Payload Upgrade Flag Command*

	Byte	Data Field
Request Data	1	Upgrade Flag. 0 = Not in upgrade mode. 1 = Payload in upgrade mode. Override boot bank swap control to be enabled.
Response Data	1	Completion Code.

## 2.6.5 Get Boot Bank Swap Control (NetFn = 0x30/0x31, CMD = 0xE4)

This command retrieves the Boot Bank Swap Control setting. When Boot Bank Swap Control is set, it disables the boot bank swap upon the BMC Watchdog Timer expiration. By default, the Boot Bank Swap Control is cleared, and boot bank will be swapped if BMC Watchdog Timer becomes expired (with action to be “hard reset”).

*Table 2-19 Get Boot Bank Swap Control Command*

	Byte	Data Field
Request Data	-	-
Response Data	1	Completion Code.
	2	Boot Bank Swap Control. 0 = Boot bank swap enabled 1 = Boot bank swap disabled

## 2.6.6 Set Boot Bank Swap Control (NetFn = 0x30/0x31, CMD = 0xE5)

This command sets the Boot Bank Swap Control setting.

*Table 2-20 Set Boot Bank Swap Control Command*

	Byte	Data Field
Request Data	1	Boot Bank Swap Control. 0 = Enable boot bank swap 1 = Disable boot bank swap
Response Data	1	Completion Code.

## 3.1 FRU Data

Following is an example of FRU Data, actual data is entered at the time of manufacturing.

```
[Common Header]
Format Version = 1

[Board Info]
Format Version = 1
Language Code = en
Mfg Date/Time = <manufacturing time>
Manufacturer = Emerson
Product Name = ATCA-F140
Serial Number = <serial number>
Part Number = <part number>
Fru File Id = 9806808E08B

[Product Info]
Format Version = 1
Language Code = en
Manufacturer = Emerson
Product Name = ATCA-F140
Part/Model Number = <serial number>
Product Version = R1.01
Serial Number = <part number>
Asset Tag =
Fru File Id = 9806808E08B

[Board Connectivity]
Format Version = 2
Vendor Format Version = 0
Group = 0
Base,1,0 = Base,0x1
Base,2,0 = Base,0x1
Base,2,0 = Base
Base,3,0 = Base
Base,4,0 = Base
Base,5,0 = Base
Base,6,0 = Base
```

```
Base,7,0 = Base
Base,8,0 = Base
Base,9,0 = Base
Base,10,0 = Base
Base,11,0 = Base
Base,12,0 = Base
Base,13,0 = Base
Base,14,0 = Base
Base,15,0 = Base
Base,16,0 = Base
Update,2,0 = {9B372D9C-7BFE-4D22-B9AD-11ABD7777CD7}
Update,2,1 = {9B372D9C-7BFE-4D22-B9AD-11ABD7777CD7}
Update,2,2 = {9B372D9C-7BFE-4D22-B9AD-11ABD7777CD7}
Update,2,3 = {9B372D9C-7BFE-4D22-B9AD-11ABD7777CD7}
Update,3,0 = {9B372D9C-7BFE-4D22-B9AD-11ABD7777CD7}
```

```
[Board Connectivity]
```

```
Format Version = 2
Vendor Format Version = 0
Group = 0
Fabric,1,0 = Ethernet
Fabric,2,0 1 2 3 = Ethernet,0x4
Fabric,2,0 1 2 3 = Ethernet,0x1
Fabric,2,0 1 2 3 = Ethernet,0x3
Fabric,2,0 1 2 3 = Ethernet
Fabric,2,0 1 = Ethernet,0x3
Fabric,2,0 1 = Ethernet
Fabric,2,0 = Ethernet,0x3
Fabric,2,0 = Ethernet
Fabric,2,0 1 2 3 = Ethernet-10Gbd,0x1
Fabric,2,0 1 2 3 = Ethernet-10Gbd
Fabric,2,0 1 = Ethernet-10Gbd
Fabric,2,0 = Ethernet-10Gbd
Fabric,3,0 1 2 3 = Ethernet,0x4
Fabric,3,0 1 2 3 = Ethernet,0x1
Fabric,3,0 1 2 3 = Ethernet,0x3
Fabric,3,0 1 2 3 = Ethernet
Fabric,3,0 1 = Ethernet,0x3
Fabric,3,0 1 = Ethernet
```

Fabric,3,0 = Ethernet,0x3  
Fabric,3,0 = Ethernet  
Fabric,3,0 1 2 3 = Ethernet-10Gbd,0x1  
Fabric,3,0 1 2 3 = Ethernet-10Gbd

Fabric,3,0 1 = Ethernet-10Gbd  
Fabric,3,0 = Ethernet-10Gbd  
Fabric,4,0 1 2 3 = Ethernet,0x4  
Fabric,4,0 1 2 3 = Ethernet,0x1  
Fabric,4,0 1 2 3 = Ethernet,0x3  
Fabric,4,0 1 2 3 = Ethernet  
Fabric,4,0 1 = Ethernet,0x3  
Fabric,4,0 1 = Ethernet  
Fabric,4,0 = Ethernet,0x3  
Fabric,4,0 = Ethernet  
Fabric,4,0 1 2 3 = Ethernet-10Gbd,0x1  
Fabric,4,0 1 2 3 = Ethernet-10Gbd  
Fabric,4,0 1 = Ethernet-10Gbd  
Fabric,4,0 = Ethernet-10Gbd  
Fabric,5,0 1 2 3 = Ethernet,0x4  
Fabric,5,0 1 2 3 = Ethernet,0x1  
Fabric,5,0 1 2 3 = Ethernet,0x3  
Fabric,5,0 1 2 3 = Ethernet  
Fabric,5,0 1 = Ethernet,0x3  
Fabric,5,0 1 = Ethernet  
Fabric,5,0 = Ethernet,0x3  
Fabric,5,0 = Ethernet  
Fabric,5,0 1 2 3 = Ethernet-10Gbd,0x1  
Fabric,5,0 1 2 3 = Ethernet-10Gbd  
Fabric,5,0 1 = Ethernet-10Gbd  
Fabric,5,0 = Ethernet-10Gbd

[Board Connectivity]

Format Version = 2

Vendor Format Version = 0

Group = 0

Fabric,6,0 1 2 3 = Ethernet,0x4

Fabric,6,0 1 2 3 = Ethernet,0x1

Fabric,6,0 1 2 3 = Ethernet,0x3

Fabric,6,0 1 2 3 = Ethernet  
Fabric,6,0 1 = Ethernet,0x3  
Fabric,6,0 1 = Ethernet  
Fabric,6,0 = Ethernet,0x3  
Fabric,6,0 = Ethernet  
Fabric,6,0 1 2 3 = Ethernet-10Gbd,0x1  
Fabric,6,0 1 2 3 = Ethernet-10Gbd  
Fabric,6,0 1 = Ethernet-10Gbd  
Fabric,6,0 = Ethernet-10Gbd  
Fabric,7,0 1 2 3 = Ethernet,0x4  
Fabric,7,0 1 2 3 = Ethernet,0x1  
Fabric,7,0 1 2 3 = Ethernet,0x3  
Fabric,7,0 1 2 3 = Ethernet  
Fabric,7,0 1 = Ethernet,0x3  
Fabric,7,0 1 = Ethernet  
Fabric,7,0 = Ethernet,0x3  
Fabric,7,0 = Ethernet  
Fabric,7,0 1 2 3 = Ethernet-10Gbd,0x1  
Fabric,7,0 1 2 3 = Ethernet-10Gbd  
Fabric,7,0 1 = Ethernet-10Gbd  
Fabric,7,0 = Ethernet-10Gbd  
Fabric,8,0 1 2 3 = Ethernet,0x4  
Fabric,8,0 1 2 3 = Ethernet,0x1  
Fabric,8,0 1 2 3 = Ethernet,0x3  
Fabric,8,0 1 2 3 = Ethernet  
Fabric,8,0 1 = Ethernet,0x3  
Fabric,8,0 1 = Ethernet  
Fabric,8,0 = Ethernet,0x3  
Fabric,8,0 = Ethernet  
Fabric,8,0 1 2 3 = Ethernet-10Gbd,0x1  
Fabric,8,0 1 2 3 = Ethernet-10Gbd  
Fabric,8,0 1 = Ethernet-10Gbd  
Fabric,8,0 = Ethernet-10Gbd  
Fabric,9,0 1 2 3 = Ethernet,0x4  
Fabric,9,0 1 2 3 = Ethernet,0x1  
Fabric,9,0 1 2 3 = Ethernet,0x3  
Fabric,9,0 1 2 3 = Ethernet  
Fabric,9,0 1 = Ethernet,0x3  
Fabric,9,0 1 = Ethernet

```
Fabric,9,0 = Ethernet,0x3
Fabric,9,0 = Ethernet
Fabric,9,0 1 2 3 = Ethernet-10Gbd,0x1
Fabric,9,0 1 2 3 = Ethernet-10Gbd
Fabric,9,0 1 = Ethernet-10Gbd
Fabric,9,0 = Ethernet-10Gbd
Fabric,10,0 1 2 3 = Ethernet,0x4
Fabric,10,0 1 2 3 = Ethernet,0x1
Fabric,10,0 1 2 3 = Ethernet,0x3
Fabric,10,0 1 2 3 = Ethernet
Fabric,10,0 1 = Ethernet,0x3
Fabric,10,0 1 = Ethernet
Fabric,10,0 = Ethernet,0x3
Fabric,10,0 = Ethernet
Fabric,10,0 1 2 3 = Ethernet-10Gbd,0x1
Fabric,10,0 1 2 3 = Ethernet-10Gbd
Fabric,10,0 1 = Ethernet-10Gbd
Fabric,10,0 = Ethernet-10Gbd
```

[Board Connectivity]

```
Format Version = 2
Vendor Format Version = 0
Group = 0
Fabric,11,0 1 2 3 = Ethernet,0x4
Fabric,11,0 1 2 3 = Ethernet,0x1
Fabric,11,0 1 2 3 = Ethernet,0x3
Fabric,11,0 1 2 3 = Ethernet
Fabric,11,0 1 = Ethernet,0x3
Fabric,11,0 1 = Ethernet
Fabric,11,0 = Ethernet,0x3
Fabric,11,0 = Ethernet
Fabric,11,0 1 2 3 = Ethernet-10Gbd,0x1
Fabric,11,0 1 2 3 = Ethernet-10Gbd
Fabric,11,0 1 = Ethernet-10Gbd
Fabric,11,0 = Ethernet-10Gbd
Fabric,12,0 1 2 3 = Ethernet,0x4
Fabric,12,0 1 2 3 = Ethernet,0x1
Fabric,12,0 1 2 3 = Ethernet,0x3
Fabric,12,0 1 2 3 = Ethernet
```

```
Fabric,12,0 1 = Ethernet,0x3
Fabric,12,0 1 = Ethernet
Fabric,12,0 = Ethernet,0x3
Fabric,12,0 = Ethernet
Fabric,12,0 1 2 3 = Ethernet-10Gbd,0x1
Fabric,12,0 1 2 3 = Ethernet-10Gbd
Fabric,12,0 1 = Ethernet-10Gbd
Fabric,12,0 = Ethernet-10Gbd
Fabric,13,0 1 2 3 = Ethernet,0x4
Fabric,13,0 1 2 3 = Ethernet,0x1
Fabric,13,0 1 2 3 = Ethernet,0x3
Fabric,13,0 1 2 3 = Ethernet
Fabric,13,0 1 = Ethernet,0x3
Fabric,13,0 1 = Ethernet
Fabric,13,0 = Ethernet,0x3
Fabric,13,0 = Ethernet
Fabric,13,0 1 2 3 = Ethernet-10Gbd,0x1
Fabric,13,0 1 2 3 = Ethernet-10Gbd
Fabric,13,0 1 = Ethernet-10Gbd
Fabric,13,0 = Ethernet-10Gbd
Fabric,14,0 = Ethernet
Fabric,15,0 = Ethernet
```

## [Carrier Info]

```
Format Version = 2
Vendor Format Version = 0
Extension Version = 2.0
Site Numbers = 5
```

## [Carrier Power]

```
Format Version = 2
Vendor Format Version = 0
Maximum Internal Current = 8.0           8.0 Amps, 96.0 Watts
Readiness = 5                            5 seconds
0x7A = 5.0                               5.0 Amps, 60.0 Watts
```



[Carrier Connectivity]

Format Version = 2

Vendor Format Version = 0

Resource = AMC 5

0 = 0, Switch 1

1 = 1, Switch 1

2 = 2, Switch 1

4 = 4, Switch 1

5 = 5, Switch 1

6 = 6, Switch 1

7 = 7, Switch 1

8 = 8, Switch 1

9 = 9, Switch 1

10 = 10, Switch 1

11 = 11, Switch 1

[Amc Connectivity]

Format Version = 2

Vendor Format Version = 0

Resource = Switch 1

Channels = 0, 1, 2, 4 5 6 7, 8 9 10 11

0,0 = AMC.2 Ethernet, 1000Base-BX

1,0 = AMC.2 Ethernet, 1000Base-BX

2,0 = AMC.3 Storage, SATA, asymm:1

3,0 1 2 3 = AMC.1 PCI Express, Gen2, asymm:1

3,0 1 2 3 = AMC.1 PCI Express, Gen1, asymm:1

3,0 1 = AMC.1 PCI Express, Gen2, asymm:1

3,0 1 = AMC.1 PCI Express, Gen1, asymm:1

3,0 = AMC.1 PCI Express, Gen2, asymm:1

3,0 = AMC.1 PCI Express, Gen2, asymm:1

4,0 1 2 3 = AMC.1 PCI Express, Gen2, asymm:1

4,0 1 2 3 = AMC.1 PCI Express, Gen1, asymm:1

4,0 1 = AMC.1 PCI Express, Gen2, asymm:1

4,0 1 = AMC.1 PCI Express, Gen1, asymm:1

4,0 = AMC.1 PCI Express, Gen2, asymm:1

4,0 = AMC.1 PCI Express, Gen1, asymm:1

[Emerson OEM Type 0x01]

```
Type = 0xc0
Manufacturer Id = 0x65cd
Data = 0x01 0x00 0x02 0x10 0x00 0x01 0x02 0x03 0x04 0x05 0x03 0x06
0x07 0x08 0x09 0x0A 0x0B
```

## 3.2 MAC Address Record

The blade provides one OEM FRU record which contains information about on-board MAC addresses. The MAC address information is stored in either of the following two ways:

- The MAC address record holds the total number of on-board MAC addresses and the base MAC address
- The MAC address record holds all on-board MAC addresses

The format of the record is described in the following table.

*Table 3-1 Artesyn MAC Addresses Record*

Offset	Length	Description
0	1	Record Type ID. A value of C0h (OEM) shall be used for Artesyn OEM records.
1	1	End of List / Version [7] End of List. Set to 1b for the last record [6:4] Reserved. Write as 000b. [3:0] Record format version. Write as 2h.
2	1	Record Length
3	1	Record Checksum (zero checksum)
4	1	Header Checksum (zero checksum)
5	1	LSB of Manufacturer ID. Write as CDh.
6	1	Second Byte of Manufacturer ID. Write as 65h.
7	1	MSB of Manufacturer ID. Write as 00h.
8	1	Artesyn Record ID. 01h for Artesyn MAC Address Record.
9	1	Record Format Version. 00h for this specification.

Table 3-1 Artesyn MAC Addresses Record

Offset	Length	Description
10	1	Number of MAC (x)
11	N=(x*7)	Artesyn MAC Address Descriptors. See <a href="#">Table 3-2 on page 35</a> .

Table 3-2 Artesyn MAC Address Descriptor

Offset	Length	Description
0	1	Interface Type. Refer to <a href="#">Table 3-3 on page 35</a> for Interface Type Assignments.
1	6	MAC Address. First Octet comes first.

Table 3-3 Interface Type Assignments

interface Type	Description
03h	Front Panel
10h	ATCA Update Channel

## 3.3 Power Configuration

Following are the power configuration details:

```
[Carrier Power]
Format Version = 2
Vendor Format Version = 0
Maximum Internal Current = 8.0           8.0 Amps, 96.0 Watts
Readiness = 5                            5 seconds
0x7A = 5.0                               5.0 Amps, 60.0 Watts
```

## 3.4 Sensor Overview

The following table lists all IPMI sensors available on the ATCA-F140.

*Table 3-4 IPMI Sensors Overview*

Sensor Number	Sensor Name	Sensor Type	Detailed SDR Description
0	Hot Swap Carrier	(PICMG) FRU Hot Swap	See <a href="#">Table 3-5 on page 38</a>
1	ATCA-F140 HS RTM	(PICMG) FRU Hot Swap	See <a href="#">Table 3-6 on page 38</a>
2	Hotswap AMC 5	(PICMG) FRU Hot Swap	See <a href="#">Table 3-7 on page 39</a>
3	Version change	Version Change	See <a href="#">Table 3-8 on page 40</a>
4	IPMB Physical	(PICMG) IPMB-0 Physical Link	See <a href="#">Table 3-9 on page 40</a>
5	BMC Watchdog	Watchdog2	See <a href="#">Table 3-10 on page 41</a>
6	12.0V	Voltage	See <a href="#">Table 3-11 on page 42</a>
7	3.3V	Voltage	See <a href="#">Table 3-12 on page 43</a>
8	1.0V FIX VDDC	Voltage	See <a href="#">Table 3-13 on page 44</a>
8	1.0V FIX VDDC	Voltage	See <a href="#">Table 3-14 on page 45</a>
9	1.0V FIX AVDD	Voltage	See <a href="#">Table 3-15 on page 46</a>
10	1.5V	Voltage	See <a href="#">Table 3-16 on page 47</a>
11	1.2V BIX	Voltage	See <a href="#">Table 3-17 on page 48</a>
12	1.05V	Voltage	See <a href="#">Table 3-18 on page 49</a>
13	1.0V	Voltage	See <a href="#">Table 3-19 on page 50</a>
14	Inlet Temp	Temperature	See <a href="#">Table 3-20 on page 51</a>
15	BIX Temp	Temperature	See <a href="#">Table 3-21 on page 51</a>
16	FIX Temp	Temperature	See <a href="#">Table 3-22 on page 52</a>
17	SP Temp	Temperature	See <a href="#">Table 3-23 on page 53</a>
18	Clock Temp	Temperature	See <a href="#">Table 3-24 on page 54</a>
19	RTM Top Temp	Temperature	See <a href="#">Table 3-25 on page 55</a>
20	RTM Mid Temp	Temperature	See <a href="#">Table 3-26 on page 56</a>
21	RTM Bottom Temp	Temperature	See <a href="#">Table 3-27 on page 57</a>

Table 3-4 IPMI Sensors Overview (continued)

Sensor Number	Sensor Name	Sensor Type	Detailed SDR Description
22	IPMC POST	Management Subsystem Health	See <a href="#">Table 3-28 on page 58</a>
23	Boot Bank	(Artesyn) OEM Type D2	See <a href="#">Table 3-29 on page 59</a>
24	SYSSTAT	(Artesyn) OEM Type CE	See <a href="#">Table 3-30 on page 60</a>
25	Fw Progress	System Firmware Progress	See <a href="#">Table 3-31 on page 60</a>
26	OS Boot	OS Boot	See <a href="#">Table 3-32 on page 61</a>
27	Boot Error	Boot Error	See <a href="#">Table 3-33 on page 62</a>
28	Boot Initiated	System Boot / Restart Initiated	See <a href="#">Table 3-34 on page 62</a>
29	ATCA-F140 IPMC	(Artesyn) OEM Type D5	See <a href="#">Table 3-35 on page 63</a>
30	Power Good	Entity Presence	See <a href="#">Table 3-36 on page 64</a>
31	-48V A Volts	Voltage	See <a href="#">Table 3-37 on page 64</a>
32	-48V B Volts	Voltage	See <a href="#">Table 3-38 on page 65</a>
33	-48V Amps	Current	See <a href="#">Table 3-39 on page 66</a>
34	HoldUp Cap Volts	Voltage	See <a href="#">Table 3-40 on page 67</a>
35	iQor Temp	Temperature	See <a href="#">Table 3-41 on page 68</a>
36	iQor Status	(Artesyn) OEM Type D7	See <a href="#">Table 3-42 on page 69</a>
37	Reset Source	(Artesyn) OEM Type D2	See <a href="#">Table 3-43 on page 70</a>
38	POST Code	(Artesyn) OEM Reserved Type FF	See <a href="#">Table 3-44 on page 71</a>
39	RTM Power Good	Power Supply	See <a href="#">Table 3-45 on page 71</a>

*Table 3-5 Hot Swap Carrier*

Feature	Raw Value	Description
Sensor Name	Hot Swap Carrier	
Sensor Number	0	
Sensor Description	Front Blade M-State	
Sensor Type Code	0xF0	(PICMG) FRU Hot Swap
Sensor Event Reading Type Code	0x6F	Sensor Specific
Assertion Event Mask	0x00FF	Assertion Event Mask: Offset 7 through 0
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x00FF	Discrete Reading Mask: State bits 0 through 7
Unit	Discrete	

*Table 3-6 ATCA-F140 HS RTM*

Feature	Raw Value	Description
Sensor Name	ATCA-F140 HS RTM	
Sensor Number	1	
Sensor Description	RTM M-State	
Sensor Type Code	0xF0	(PICMG) FRU Hot Swap
Sensor Event Reading Type Code	0x6F	Sensor Specific
Assertion Event Mask	0x00FF	Assertion Event Mask: Offset 7 through 0

Table 3-6 ATCA-F140 HS RTM

Feature	Raw Value	Description
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x00FF	Discrete Reading Mask: State bits 0 through 7
Unit	Discrete	

Table 3-7 Hotswap AMC 5

Feature	Raw Value	Description
Sensor Name	Hotswap AMC 5	
Sensor Number	2	
Sensor Description	AMC (Site 5) M-State	
Sensor Type Code	0xF0	(PICMG) FRU Hot Swap
Sensor Event Reading Type Code	0x6F	Sensor Specific
Assertion Event Mask	0x00FF	Assertion Event Mask: Offset 7 through 0
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x00FF	Discrete Reading Mask: State bits 0 through 7
Unit	Discrete	

*Table 3-8 Version change*

Feature	Raw Value	Description
Sensor Name	Version change	
Sensor Number	3	
Sensor Description	IPMC Firmware Version Change	
Sensor Type Code	0x2B	Version Change
Sensor Event Reading Type Code	0x6F	Sensor Specific
Assertion Event Mask	0x00FF	Assertion Event Mask: Offset 7 through 0
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x00FF	Discrete Reading Mask: State bits 0 through 7
Unit	Discrete	

*Table 3-9 IPMB Physical*

Feature	Raw Value	Description
Sensor Name	IPMB Physical	
Sensor Number	4	
Sensor Description	IPMB-0 Link State	
Sensor Type Code	0xF1	(PICMG) IPMB-0 Physical Link
Sensor Event Reading Type Code	0x6F	Sensor Specific



*Table 3-9 IPMB Physical*

Feature	Raw Value	Description
Assertion Event Mask	0x000F	Assertion Event Mask: Offset 3 through 0
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x000F	Discrete Reading Mask: State bits 0 through 3
Unit	Discrete	

*Table 3-10 BMC Watchdog*

Feature	Raw Value	Description
Sensor Name	BMC Watchdog	
Sensor Number	5	
Sensor Description	BMC Watchdog	
Sensor Type Code	0x23	Watchdog2
Sensor Event Reading Type Code	0x6F	Sensor Specific
Assertion Event Mask	0x0000	Assertion Event Mask: None
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x010F	Discrete Reading Mask: State bit 0, 1, 2, 3, and 8
Unit	Discrete	

*Table 3-11 12.0V Sensor*

Feature	Raw Value	Description
Sensor Name	12.0V	
Sensor Number	6	
Sensor Description	Main Payload Power	
Sensor Type Code	0x02	Voltage
Sensor Event Reading Type Code	0x01	Threshold
Lower Threshold Reading Mask Code	0x6A14	Lower Threshold Reading Mask: LNR, LC Assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Upper Threshold Reading Mask Code	0x6A14	Upper Threshold Reading Mask: UNR, UC De-assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Settable Threshold Mask, Readable Threshold Mask Code	0x3636	Settable Threshold Mask: UNR, UC, LNR, LC Readable Threshold Mask: UNR, UC, LNR, LC
Unit	Volts	

Table 3-12 3.3V Sensor

Feature	Raw Value	Description
Sensor Name	3.3V	
Sensor Number	7	
Sensor Description	Internal Voltage	
Sensor Type Code	0x02	Voltage
Sensor Event Reading Type Code	0x01	Threshold
Lower Threshold Reading Mask Code	0x6A14	Lower Threshold Reading Mask: LNR, LC Assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Upper Threshold Reading Mask Code	0x6A14	Upper Threshold Reading Mask: UNR, UC De-assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Settable Threshold Mask, Readable Threshold Mask Code	0x3636	Settable Threshold Mask: UNR, UC, LNR, LC Readable Threshold Mask: UNR, UC, LNR, LC
Unit	Volts	

Table 3-13 1.0V FIX VDDC

Feature	Raw Value	Description
Sensor Name	1.0V FIX VDDC	
Sensor Number	8	
Sensor Description	Internal Voltage (Trident AVS status = 0x01, ROV=1.025V)	
Sensor Type Code	0x02	Voltage
Sensor Event Reading Type Code	0x01	Threshold
Lower Threshold Reading Mask Code	0x6A14	Lower Threshold Reading Mask: LNR, LC Assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Upper Threshold Reading Mask Code	0x6A14	Upper Threshold Reading Mask: UNR, UC De-assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Settable Threshold Mask, Readable Threshold Mask Code	0x3636	Settable Threshold Mask: UNR, UC, LNR, LC Readable Threshold Mask: UNR, UC, LNR, LC
Unit	Volts	

Table 3-14 1.0V FIX VDDC

Features	Raw Value	Description
Sensor Name	1.0V FIX VDDC	
Sensor Number	8	
Sensor Description	Internal Voltage (Trident AVS status = 0x02, ROV=0.90V)	
Sensor Type Code	0x02	Voltage
Sensor Event Reading Type Code	0x01	Threshold
Lower Threshold Reading Mask Code	0x6A14	Lower Threshold Reading Mask: LNR, LC Assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Upper Threshold reading Mask Code	0x6A14	Upper Threshold Reading Mask: UNR, UC De-assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Settable Threshold Mask, Readable Threshold Mask Code	0x3636	Settable Threshold Mask: UNR, UC, LNR, LC Readable Threshold Mask: UNR, UC, LNR, LC
Unit	Volts	

*Table 3-15 1.0V FIX AVDD*

Features	Raw Value	Description
Sensor Name	1.0V FIX AVDD	
Sensor Number	9	
Sensor Description	Internal Voltage	
Sensor Type Code	0x02	Voltage
Sensor Event Reading Type Code	0x01	Threshold
Lower Threshold reading Mask Code	0x6A14	Lower Threshold Reading Mask: LNR, LC Assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Upper Threshold reading Mask Code	0x6A14	Upper Threshold Reading Mask: UNR, UC De-assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Settable Threshold Mask, Readable Threshold Mask Code	0x3636	Settable Threshold Mask: UNR, UC, LNR, LC Readable Threshold Mask: UNR, UC, LNR, LC
Unit	Volts	

Table 3-16 1.5V

Features	Raw Value	Description
Sensor Name	1.5V	
Sensor Number	10	
Sensor Description	Internal Voltage	
Sensor Type Code	0x02	Voltage
Sensor Event Reading Type Code	0x01	Threshold
Lower Threshold reading Mask Code	0x6A14	Lower Threshold Reading Mask: LNR, LC Assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Upper Threshold reading Mask Code	0x6A14	Upper Threshold Reading Mask: UNR, UC De-assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Settable Threshold Mask, Readable Threshold Mask Code	0x3636	Settable Threshold Mask: UNR, UC, LNR, LC Readable Threshold Mask: UNR, UC, LNR, LC
Unit	Volts	

*Table 3-17 1.2V BIX*

Features	Raw Value	Description
Sensor Name	1.2V BIX	
Sensor Number	11	
Sensor Description	Internal Voltage	
Sensor Type Code	0x02	Voltage
Sensor Event Reading Type Code	0x01	Threshold
Lower Threshold reading Mask Code	0x6A14	Lower Threshold Reading Mask: LNR, LC Assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Upper Threshold reading Mask Code	0x6A14	Upper Threshold Reading Mask: UNR, UC De-assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Settable Threshold Mask, Readable Threshold Mask Code	0x3636	Settable Threshold Mask: UNR, UC, LNR, LC Readable Threshold Mask: UNR, UC, LNR, LC
Unit	Volts	



Table 3-18 1.05V

Features	Raw Value	Description
Sensor Name	1.05V	
Sensor Number	12	
Sensor Description	Internal Voltage	
Sensor Type Code	0x02	Voltage
Sensor Event Reading Type Code	0x01	Threshold
Lower Threshold reading Mask Code	0x6A14	Lower Threshold Reading Mask: LNR, LC Assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Upper Threshold reading Mask Code	0x6A14	Upper Threshold Reading Mask: UNR, UC De-assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Settable Threshold Mask, Readable Threshold Mask Code	0x3636	Settable Threshold Mask: UNR, UC, LNR, LC Readable Threshold Mask: UNR, UC, LNR, LC
Unit	Volts	

*Table 3-19 1.0V*

Features	Raw Value	Description
Sensor Name	1.0V	
Sensor Number	13	
Sensor Description	Internal Voltage	
Sensor Type Code	0x02	Voltage
Sensor Event Reading Type Code	0x01	Threshold
Lower Threshold reading Mask Code	0x6A14	Lower Threshold Reading Mask: LNR, LC Assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Upper Threshold reading Mask Code	0x6A14	Upper Threshold Reading Mask: UNR, UC De-assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Settable Threshold Mask, Readable Threshold Mask Code	0x3636	Settable Threshold Mask: UNR, UC, LNR, LC Readable Threshold Mask: UNR, UC, LNR, LC
Unit	Volts	

Table 3-20 Inlet Temp

Features	Raw Value	Description
Sensor Name	Inlet Temp	
Sensor Number	14	
Sensor Description	Inlet Air Temperature	
Sensor Type Code	0x01	Temperature
Sensor Event Reading Type Code	0x01	Threshold
Lower Threshold reading Mask Code	0x0A80	Lower Threshold Reading Mask: None Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Upper Threshold reading Mask Code	0x7A80	Upper Threshold Reading Mask: UNR, UC, UNC Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Settable Threshold Mask, Readable Threshold Mask Code	0x3838	Settable Threshold Mask: UNR, UC, UNC Readable Threshold Mask: UNR, UC, UNC
Unit	degrees C	

Table 3-21 BIX Temp

Features	Raw Value	Description
Sensor Name	BIX Temp	

*Table 3-21 BIX Temp*

Features	Raw Value	Description
Sensor Number	15	
Sensor Description	BIX Temperature	
Sensor Type Code	0x01	Temperature
Sensor Event Reading Type Code	0x01	Threshold
Lower Threshold reading Mask Code	0x0A80	Lower Threshold Reading Mask: None Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Upper Threshold reading Mask Code	0x7A80	Upper Threshold Reading Mask: UNR, UC, UNC Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Settable Threshold Mask, Readable Threshold Mask Code	0x3838	Settable Threshold Mask: UNR, UC, UNC Readable Threshold Mask: UNR, UC, UNC
Unit	degrees C	

*Table 3-22 FIX Temp*

Features	Raw Value	Description
Sensor Name	FIX Temp	
Sensor Number	16	
Sensor Description	FIX Temperature	
Sensor Type Code	0x01	Temperature

Table 3-22 FIX Temp

Features	Raw Value	Description
Sensor Event Reading Type Code	0x01	Threshold
Lower Threshold reading Mask Code	0x0A80	Lower Threshold Reading Mask: None Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Upper Threshold reading Mask Code	0x7A80	Upper Threshold Reading Mask: UNR, UC, UNC Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Settable Threshold Mask, Readable Threshold Mask Code	0x3838	Settable Threshold Mask: UNR, UC, UNC Readable Threshold Mask: UNR, UC, UNC
Unit	degrees C	

Table 3-23 SP Temp

Features	Raw Value	Description
Sensor Name	SP Temp	
Sensor Number	17	
Sensor Description	SP Temperature	
Sensor Type Code	0x01	Temperature
Sensor Event Reading Type Code	0x01	Threshold

*Table 3-23 SP Temp*

Features	Raw Value	Description
Lower Threshold reading Mask Code	0x0A80	Lower Threshold Reading Mask: None Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Upper Threshold reading Mask Code	0x7A80	Upper Threshold Reading Mask: UNR, UC, UNC Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Settable Threshold Mask, Readable Threshold Mask Code	0x3838	Settable Threshold Mask: UNR, UC, UNC Readable Threshold Mask: UNR, UC, UNC
Unit	degrees C	

*Table 3-24 Clock Temp*

Features	Raw Value	Description
Sensor Name	Clock Temp	
Sensor Number	18	
Sensor Description	Clock Temperature	
Sensor Type Code	0x01	Temperature
Sensor Event Reading Type Code	0x01	Threshold

Table 3-24 Clock Temp

Features	Raw Value	Description
Lower Threshold reading Mask Code	0x0A80	Lower Threshold Reading Mask: None Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Upper Threshold reading Mask Code	0x7A80	Upper Threshold Reading Mask: UNR, UC, UNC Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Settable Threshold Mask, Readable Threshold Mask Code	0x3838	Settable Threshold Mask: UNR, UC, UNC Readable Threshold Mask: UNR, UC, UNC
Unit	degrees C	

Table 3-25 RTM Top Temp

Features	Raw Value	Description
Sensor Name	RTM Top Temp	
Sensor Number	19	
Sensor Description	RTM Top Area Temperature	
Sensor Type Code	0x01	Temperature
Sensor Event Reading Type Code	0x01	Threshold

*Table 3-25 RTM Top Temp*

Features	Raw Value	Description
Lower Threshold reading Mask Code	0x0A80	Lower Threshold Reading Mask: None Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Upper Threshold reading Mask Code	0x7A80	Upper Threshold Reading Mask: UNR, UC, UNC Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Settable Threshold Mask, Readable Threshold Mask Code	0x3838	Settable Threshold Mask: UNR, UC, UNC Readable Threshold Mask: UNR, UC, UNC
Unit	degrees C	

*Table 3-26 RTM Mid Temp*

Features	Raw Value	Description
Sensor Name	RTM Mid Temp	
Sensor Number	20	
Sensor Description	RTM Middle Area Temperature	
Sensor Type Code	0x01	Temperature
Sensor Event Reading Type Code	0x01	Threshold



Table 3-26 RTM Mid Temp

Features	Raw Value	Description
Lower Threshold reading Mask Code	0x0A80	Lower Threshold Reading Mask: None Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Upper Threshold reading Mask Code	0x7A80	Upper Threshold Reading Mask: UNR, UC, UNC Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Settable Threshold Mask, Readable Threshold Mask Code	0x3838	Settable Threshold Mask: UNR, UC, UNC Readable Threshold Mask: UNR, UC, UNC
Unit	degrees C	

Table 3-27 RTM Bottom Temp

Features	Raw Value	Description
Sensor Name	RTM Bottom Temp	
Sensor Number	21	
Sensor Description	RTM Bottom Inlet Air Temperature	
Sensor Type Code	0x01	Temperature
Sensor Event Reading Type Code	0x01	Threshold

*Table 3-27 RTM Bottom Temp*

Features	Raw Value	Description
Lower Threshold reading Mask Code	0x0A80	Lower Threshold Reading Mask: None Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Upper Threshold reading Mask Code	0x7A80	Upper Threshold Reading Mask: UNR, UC, UNC Assertion Event Mask: UNR-GH, UC-GH, UNC-GH
Settable Threshold Mask, Readable Threshold Mask Code	0x3838	Settable Threshold Mask: UNR, UC, UNC Readable Threshold Mask: UNR, UC, UNC
Unit	degrees C	

*Table 3-28 IPMC POST*

Features	Raw Value	Description
Sensor Name	IPMC POST	
Sensor Number	22	
Sensor Description	IPMC Firmware POST	
Sensor Type Code	0x28	Management Subsystem Health
Sensor Event Reading Type Code	0x06	Discrete Performance
Assertion Event Mask	0x0003	Assertion Event Mask: Offset 1 and 0

*Table 3-28 IPMC POST*

Features	Raw Value	Description
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x0003	Discrete Reading Mask: State bit 0 and 1
Unit	Discrete	

*Table 3-29 Boot Bank*

Features	Raw Value	Description
Sensor Name	Boot Bank	
Sensor Number	23	
Sensor Description	Boot Firmware Flash Bank Selection and FPGA Bank Selection	
Sensor Type Code	0xD2	(Artesyn) OEM Type D2
Sensor Event Reading Type Code	0x6F	Sensor Specific
Assertion Event Mask	0x0003	Assertion Event Mask: Offset 1 and 0
De-assertion Event Mask	0x0003	De-assertion Event Mask: Offset 1 and 0
Discrete Reading Mask	0x0003	Discrete Reading Mask: State bit 0 and 1
Unit	Discrete	

*Table 3-30 Reserved*

Features	Raw Value	Description
Sensor Name	SYSTAT	
Sensor Number	24	
Sensor Description	Reserved	System Status
Sensor Type Code	0xCE	(Artesyn) OEM Type CE.
Sensor Event Reading Type Code	0x07	Discrete State
Assertion Event Mask	0x000F	Assertion Event Mask: Offset 3 through 0
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x000F	Discrete Reading Mask: State bit 0 through 3
Unit	Discrete	

*Table 3-31 Fw Progress*

Features	Raw Value	Description
Sensor Name	Fw Progress	
Sensor Number	25	
Sensor Description	Boot Firmware Progress	
Sensor Type Code	0x0F	System Firmware Progress
Sensor Event Reading Type Code	0x6F	Sensor Specific

Table 3-31 Fw Progress

Features	Raw Value	Description
Assertion Event Mask	0x0007	Assertion Event Mask: Offset 2, 1, and 0
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x0007	Discrete Reading Mask: State bit 0, 1, and 2
Unit	Discrete	

Table 3-32 OS Boot

Features	Raw Value	Description
Sensor Name	OS Boot	
Sensor Number	26	
Sensor Description	OS Boot	
Sensor Type Code	0x1F	OS Boot
Sensor Event Reading Type Code	0x6F	Sensor Specific
Assertion Event Mask	0x007F	Assertion Event Mask: Offset 6 through 0
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x007F	Discrete Reading Mask: State bits 0 through 6
Unit	Discrete	

*Table 3-33 Boot Error*

Features	Raw Value	Description
Sensor Name	Boot Error	
Sensor Number	27	
Sensor Description	Boot Error	
Sensor Type Code	0x1E	Boot Error
Sensor Event Reading Type Code	0x6F	Sensor Specific
Assertion Event Mask	0x001F	Assertion Event Mask: Offset 4 through 0
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x001F	Discrete Reading Mask: State bits 0 through 4
Unit	Discrete	

*Table 3-34 Boot Initiated*

Features	Raw Value	Description
Sensor Name	Boot Initiated	
Sensor Number	28	
Sensor Description	Boot Initiated	
Sensor Type Code	0x1D	System Boot / Restart Initiated
Sensor Event Reading Type Code	0x6F	Sensor Specific
Assertion Event Mask	0x001F	Assertion Event Mask: Offset 4 through 0

*Table 3-34 Boot Initiated*

Features	Raw Value	Description
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x001F	Discrete Reading Mask: State bits 0 through 4
Unit	Discrete	

*Table 3-35 ATCA-F140 IPMC*

Features	Raw Value	Description
Sensor Name	ATCA-F140 IPMC	
Sensor Number	29	
Sensor Description	IPMC Reset Cause	
Sensor Type Code	0xD5	(Artesyn) OEM Type D5
Sensor Event Reading Type Code	0x6F	Sensor Specific
Assertion Event Mask	0x0000	Assertion Event Mask: None
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x007F	Discrete Reading Mask: State bits 0 through 6
Unit	Discrete	

*Table 3-36 Power Good*

Features	Raw Value	Description
Sensor Name	Power Good	
Sensor Number	30	
Sensor Description	All Power Good Indicator	
Sensor Type Code	0x25	Entity Presence
Sensor Event Reading Type Code	0x6F	Sensor Specific
Assertion Event Mask	0x0003	Assertion Event Mask: Offset 1 and 0
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x0003	Discrete Reading Mask: State bit 0 and 1
Unit	Discrete	

*Table 3-37 -48V A Volts*

Features	Raw Value	Description
Sensor Name	-48V A Volts	
Sensor Number	31	
Sensor Description	-48V Input A Voltage	
Sensor Type Code	0x02	Voltage
Sensor Event Reading Type Code	0x01	Threshold



Table 3-37 -48V A Volts

Features	Raw Value	Description
Lower Threshold reading Mask Code	0x6A14	Lower Threshold Reading Mask: LNR, LC Assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Upper Threshold reading Mask Code	0x6A14	Upper Threshold Reading Mask: UNR, UC De-assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Settable Threshold Mask, Readable Threshold Mask Code	0x3636	Settable Threshold Mask: UNR, UC, LNR, LC Readable Threshold Mask: UNR, UC, LNR, LC
Unit	Volts	

Table 3-38 -48V B Volts

Features	Raw Value	Description
Sensor Name	-48V B Volts	
Sensor Number	32	
Sensor Description	-48V Input B Voltage	
Sensor Type Code	0x02	Voltage
Sensor Event Reading Type Code	0x01	Threshold

*Table 3-38 -48V B Volts*

Features	Raw Value	Description
Lower Threshold reading Mask Code	0x6A14	Lower Threshold Reading Mask: LNR, LC Assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Upper Threshold reading Mask Code	0x6A14	Upper Threshold Reading Mask: UNR, UC De-assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Settable Threshold Mask, Readable Threshold Mask Code	0x3636	Settable Threshold Mask: UNR, UC, LNR, LC Readable Threshold Mask: UNR, UC, LNR, LC
Unit	Volts	

*Table 3-39 -48V Amps*

Features	Raw Value	Description
Sensor Name	-48V Amps	
Sensor Number	33	
Sensor Description	-48V Input Current	
Sensor Type Code	0x03	Current
Sensor Event Reading Type Code	0x01	Threshold

Table 3-39 -48V Amps

Features	Raw Value	Description
Lower Threshold reading Mask Code	0x0000	Lower Threshold Reading Mask: None Assertion Event Mask: None
Upper Threshold reading Mask Code	0x0000	Upper Threshold Reading Mask: None De-assertion Event Mask: None
Settable Threshold Mask, Readable Threshold Mask Code	0x0000	Settable Threshold Mask: None Readable Threshold Mask: None
Unit	Amps	

Table 3-40 HoldUp Cap Volts

Features	Raw Value	Description
Sensor Name	HoldUp Cap Volts	
Sensor Number	34	
Sensor Description	Power Module Holdup Cap Voltage	
Sensor Type Code	0x02	Voltage
Sensor Event Reading Type Code	0x01	Threshold

*Table 3-40 HoldUp Cap Volts*

Features	Raw Value	Description
Lower Threshold reading Mask Code	0x6A14	Lower Threshold Reading Mask: LNR, LC Assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Upper Threshold reading Mask Code	0x6A14	Upper Threshold Reading Mask: UNR, UC De-assertion Event Mask: UNR-GH, UC-GH, LNR-GL, LC-GL
Settable Threshold Mask, Readable Threshold Mask Code	0x3636	Settable Threshold Mask: UNR, UC, LNR, LC Readable Threshold Mask: UNR, UC, LNR, LC
Unit	Volts	

*Table 3-41 iQor Temp*

Features	Raw Value	Description
Sensor Name	iQor Temp	
Sensor Number	35	
Sensor Description	Power Module Temperature	
Sensor Type Code	0x01	Temperature
Sensor Event Reading Type Code	0x01	Threshold

Table 3-41 iQor Temp

Features	Raw Value	Description
Lower Threshold reading Mask Code	0x0000	Lower Threshold Reading Mask: None Assertion Event Mask: None
Upper Threshold reading Mask Code	0x0000	Upper Threshold Reading Mask: None De-assertion Event Mask: None
Settable Threshold Mask, Readable Threshold Mask Code	0x3838	Settable Threshold Mask: UNR, UC, UNC Readable Threshold Mask: UNR, UC, UNC
Unit	degrees C	

---

Note: By default, iQor Temp is a read-only sensor. Hence, the thresholds for this sensor are disabled and it does not generate any event.

---

Table 3-42 iQor Status

Features	Raw Value	Description
Sensor Name	iQor Status	
Sensor Number	36	
Sensor Description	Power Module Status	
Sensor Type Code	0xD7	(Artesyn) OEM Type D7
Sensor Event Reading Type Code	0x6F	Sensor Specific

*Table 3-42 iQor Status*

Features	Raw Value	Description
Assertion Event Mask	0x0077	Assertion Event Mask: Offset 6, 5, 4, 2, 1, and 0
De-assertion Event Mask	0x0077	De-assertion Event Mask: Offset 6, 5, 4, 2, 1, and 0
Discrete Reading Mask	0x0077	Discrete Reading Mask: Offset 6, 5, 4, 2, 1, and 0
Unit	Discrete	

*Table 3-43 Reset Source*

Features	Raw Value	Description
Sensor Name	Reset Source	
Sensor Number	37	
Sensor Description	Reset Source Indicator	
Sensor Type Code	0xD2	(Artesyn) OEM Type D2
Sensor Event Reading Type Code	0x6F	Sensor Specific
Assertion Event Mask	0x00FF	Assertion Event Mask: Offset 7 through 0
De-assertion Event Mask	0x00FF	De-assertion Event Mask: None
Discrete Reading Mask	0x00FF	Discrete Reading Mask: State bits 0 through 7
Unit	Discrete	

Table 3-44 POST Code

Features	Raw Value	Description
Sensor Name	POST Code	
Sensor Number	38	
Sensor Description	Reserved	
Sensor Type Code	0xFF	(Artesyn) OEM Reserved Type FF
Sensor Event Reading Type Code	0x03	Sensor Specific
Assertion Event Mask	0x0000	Assertion Event Mask: None
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x0000	Discrete Reading Mask: None
Unit	Discrete	

Table 3-45 RTM Power Good

Features	Raw Value	Description
Sensor Name	RTM Power Good	
Sensor Number	39	
Sensor Description	RTM Power Good Indicator	
Sensor Type Code	0x08	Power Supply
Sensor Event Reading Type Code	0x03	Discrete State

*Table 3-45 RTM Power Good*

Features	Raw Value	Description
Assertion Event Mask	0x0003	Assertion Event Mask: Offset 1 and 0
De-assertion Event Mask	0x0000	De-assertion Event Mask: None
Discrete Reading Mask	0x0003	Discrete Reading Mask: State bit 0 and 1
Unit	Discrete	



# OEM Sensors

## 4.1 OEM Sensors

This section describes the various OEM sensors provided by Artesyn that are located on the ATCA-F140.

Table 4-1 OEM Sensor

Sensor Number	Sensor Name	Sensor Type Code	Sensor Type	Sensor Event Reading Type Code	Sensor Event Reading Type	Description
23	Boot Bank	0xD2	(Artesyn) OEM Type D2	0x6F	Sensor Specific	Current FPGA boot bank and next Boot Firmware bank Offset 0: Next Boot Firmware Bank (1: Bank B, 0: Bank A) Offset 1: Current FPGA Bank Booted From (1: Golden Bank, 0: Default Active Bank)
24	SYSSTAT	0xCE	(Artesyn) OEM Type CE	0x07	Discrete Severity	System Status reported by SYSSTATMGR running on payload Offset 0: OK. No errors. Offset 1: Non-Critical. Offset 2: Critical. Offset 3: Non-Recoverable. Event Data 2: system status monitor identifier. Event Data 3: system status modifier.
29	ATCA-F140 IPMC	0xD5	(Artesyn) OEM Type D5	0x6F	Sensor Specific	IPMC firmware reset cause. (Read-Only, No SEL Events) Offset 0: Watchdog Triggered Reset Offset 1: Software Caused Reset (e.g. firmware upgrade) Offset 2: Power Failure Caused Reset (All other offsets may not be correct in this release) Offset 3: External Reset Offset 4: Hard Reset Offset 5: Cold Reset Offset 6: Warm Reset

Table 4-1 OEM Sensor (continued)

Sensor Number	Sensor Name	Sensor Type Code	Sensor Type	Sensor Event Reading Type Code	Sensor Event Reading Type	Description
36	iQor Status	0xD7	(Artesyn) OEM Type D7	0x6F	Sensor Specific	Power Module Status: Event Data 0 = 0xA0, Event Data 2 = Status, Event Data 3 = 0x00 Offset 0 (bit 0): Enable A Signal State (1: Enabled) Offset 1 (bit 1): Enable B Signal State (1: Enabled) Offset 2 (bit 2): Alarm Signal State (Primary Side Alarm Set) Offset 3 (bit 3): Reserved Offset 4 (bit 4): Holdup Switch State (1: Holdup Cap is Connected to -49V Out) Offset 5 (bit 5): Hotswap Switch State (1: Hotswap Switch is ON) Offset 6 (bit 6): -48V Output Under-Voltage Alarm (1: Output Voltage is above Threshold) Offset 7 (bit 7): Reserved
37	Reset Source	0xD2	(Artesyn) OEM Type D2	0x6F	Sensor Specific	FPGA Reset Cause Register. Sensor Reading = Event Data 2 = Cause Register Offset 0 (bit 0): Initial Watchdog Timer Reset Offset 1 (bit 1): Two-stage Watchdog Timer Reset Offset 2 (bit 2): Push Button Reset Offset 3 (bit 3): FPGA Reset Register Initiated Reset Offset 4 (bit 4): IPMC Initiated Reset Offset 5 (bit 5): Service Processor Initiated Reset Offset 6 (bit 6): Emulator Initiated Reset Offset 7 (bit 7): Power-On Reset
38	POST Code	0xFF	(Artesyn) OEM Reserved Type FF	0x6F	Sensor Specific	Not used. Placeholder Sensor.

# Related Documentation

## A.1 Artesyn Embedded Technologies - Embedded Computing Documentation

The publications listed below are referenced in this manual. You can obtain electronic copies of Artesyn Embedded Technologies - Embedded Computing publications by contacting your local Artesyn sales office. For released products, you can also visit our Web site for the latest copies of our product documentation.

1. Go to [www.artesyn.com/computing/support/product/technical-documentation.php](http://www.artesyn.com/computing/support/product/technical-documentation.php).
2. Under **FILTER OPTIONS**, click the Document types drop-down list box to select the type of document you are looking for.
3. In the **Search** text box, type the product name and click **GO**.

*Table A-1 Artesyn Embedded Technologies - Embedded Computing Publications*

Document Title	Publication Number
ATCA-F140 Installation and Use	6806800M67
Basic Blade Services Software on ATCA-F140 Programmer's Reference	6806800N23

## A.2 Related Specifications

For additional information, refer to the following table for related specifications. As an additional help, a source for the listed document is provided. Please note that, while these sources have been verified, the information is subject to change without notice.

*Table A-2 Related Specifications*

Document Title	Source
Pigeon Point Shelf Manager User Guide	
Pigeon Point Shelf Manager External Interface Reference	
IPMI Specifications, <a href="http://www.intel.com/design/servers/ipmi">http://www.intel.com/design/servers/ipmi</a>	
IPMI Spec v1.5, Document Revision 1.1, February 20, 2002	Intel Corporation, Hewlett-Packard, DEC, NEC
IPMI v1.5 Addenda, Errata, and Clarifications, Addendum Document Revision 5, January 29, 2004	Intel Corporation, Hewlett-Packard, DEC, NEC

*Table A-2 Related Specifications (continued)*

Document Title	Source
Intelligent Platform Management Interface Specification v1.0, Document Revision 1.1, November 15 1999	Intel Corporation, Hewlett-Packard, NEC, Dell
IPMI Implementer's Guide, Draft Version 0.7, September 16, 1998	Intel Corporation
IPMI Platform Management FRU Information Storage Definition V1.0, September 27, 1999	Intel Corporation
PCI Industrial Manufacturers Group (PICMG) <a href="http://www.picmg.com/">http://www.picmg.com/</a>	
AdvancedTCA Base 3.0 Specification, Revision 3.0, March 24, 2008	PICMG 3.0 R 3.0
Advanced Mezzanine Card Base Specification, R2.0, November 15, 2006	AMC.0 Rev 2.0
Hardware Platform Management IPM Controller Firmware Upgrade Specification, R1.0, June 01, 2007	HPM.1 Rev 1.0





Artesyn Embedded Technologies, Artesyn and the Artesyn Embedded Technologies logo are trademarks and service marks of Artesyn Embedded Technologies, Inc. All other product or service names are the property of their respective owners.

© 2017 Artesyn Embedded Technologies, Inc.