

AXP1440 & Centellis® 4440 Bladed Server Platform

Data Sheet

The AXP1440 and Centellis® 4440 40G ATCA systems are specifically designed to address the unique requirements of defense and networking applications

- Architected for high availability applications
- CP-TA B.4 compliant thermal performance
- Up to 350W per blade power distribution
- Redundant shelf management and alarms
- 12 payload & 2 switching slots with rear transition module capability for each slot
- PICMG 3.0 ATCA mechanical formfactor and power/cooling design
- PICMG 3.1 ATCA high performance switch fabric capable of 1, 10, and 40Gbps operation

The AXP1440 is a rugged high-availability ATCA® chassis with a rich ecosystem of blades and software suited to defense, security and networking applications. The chassis is available configured with redundant 40G switch blades as the Centellis® 4440

Benefits

- Bladed architecture for scalability, minimized cabling and ease of maintenance
- Application-ready configurations shorten time-to-market
- Strong ecosystem of off-the-shelf or custom blades allows the platform to be easily configured for a range of applications & upgraded as new technologies become available



Advanced TCA®

Rich Content Ecosystem

- Advanced load balancing and packet classification software
- Intel Xeon-based server blades with storage options
- High throughput packet processing blades based on Cavium Octeon or Intel Architecture processors
- 40G & 10G switching blades with system control functionality

Enclosure

- 14 blade slots each with rear transition module (RTM) slots
 - 2 switch/system manager slots
 - 12 8U payload slots for application blades
- 40/10/1G-capable backplane delivering up to 80G fabric bandwidth to each slot
- Dual shelf managers and alarm modules
- Front Alarm Display Panel (ADP)
 - Two COM ports (one for each shelf manager)
 - Telco alarm indicators (PWR, Minor, Major, Critical)
 - Alarm reset
 - Telco Alarm interface (dry relay contact, DB-15)
- Front-to-rear cooling
 - Redundant fan trays – one bottom fan tray, one top fan tray
- Cable Management System
- Enclosure Dimensions & Weight
 - 573 mm high x 449 mm wide (not including mounting ears) x 544 mm deep
 - Weight: 39.7 kg / 87.5 Lbs.
- Operating Environment
 - Operating temperature range (DC): -5°C to 55°C @ 90% non-condensing humidity
 - Storage temperature range: -40°C to 70°C @ 95% non-condensing humidity

Fabric Switch

Centellis 4440 includes redundant 40G Ethernet ATCA-F140 switch blades providing the communications fabric. The switch blades also include OPTIONAL system management functionality.

- ATCA 1G, 10G, 40G fabric switch interface in dual star topology
- Integrated Linux-based software package for system & switch management
- Customization options with AMC site, disk bay and telecom clocking function
- Available FlowPilot load balancing software
- Face plate interfaces
 - Service processor interface via 1G Ethernet (RJ-45) and RS-232 serial
 - Base interface via 1G/10G Ethernet (SFP+) ports
 - Fabric interface via 1G/10G and 40G Ethernet ports (SFP+ and QSFP+)
 - Telecom Clock interfaces
- Blade Services Software
 - Linux OS
 - Firmware Upgrade Facility
 - Hardware Platform Interface (HPI) to manage platform elements configured for multi-shelf management support
 - SRstackware® switching software including switch chip initialization, configuration, management as well as a full suite of L2 and L3 protocols

The Artesyn Experience

Artesyn has over 30 years of experience serving the defense and telecommunications industries and has hundreds of thousands of products deployed in the world's communications networks and defense systems. With that long experience comes a deep understanding of our customers' requirements for on-time, consistent and high quality product coupled with excellent customer support. We deliver on all counts from our own world-class factory and seasoned support experts.

We're very flexible and agile. We recognize that you may need your system to have your own unique branding. No problem. We're used to that. We have services that allow you to define the look and feel that's consistent with your company's branding and aesthetic standards. Our flexibility isn't just limited to look and feel. Integration services, unique support requirements, longevity of supply, drop shipments and many more services are designed to make it easy to do business with us and quick for you to get to market and deploy smoothly.

Regulatory Compliance

Item	Description
Designed to comply with NEBS	GR-63-CORE, NEBS Physical Protection, Level 3
	GR-1089-CORE, Electromagnetic Compatibility and Electrical Safety — Generic Criteria for Network Telecommunications Equipment. Level 3, Equipment Type 2
Designed to comply with ETSI	ETSI Storage, ETS 300 019-2-1, Class 1.2 equipment, Not Temperature Controlled Storage Locations
	ETSI Transportation, ETS 300 019-2-2, Class 2.3 equipment, Public Transportation
	ETS 300-132-2 Environmental Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 2: Operated by direct current (dc)
	ETSI Operation, ETS 300 019-2-3, Class 3.1 equipment, Partly Temperature Controlled Locations
Designed to comply with Acoustic	ETS-300-753, Equipment Engineering (EE); Acoustic noise emitted by telecommunications equipment
EMC	EN-300-386 Electromagnetic compatibility and Radio spectrum Matters (ERM); telecommunication network equipment; ElectroMagnetic Compatibility (EMC) requirements, Telecommunication equipment room (attended)
	FCC 47 CFR Part 15 Subpart B (US), Class A
	EMC Directive 89/336/EEC (EU)
	AS/NZS 3548 (Australia/New Zealand), Limits and Methods of Measurement of Radio Disturbance Characteristics of Information Technology Equipment
	VCCI Class A (Japan), Voluntary Control Council for Interference by Information Technology Equipment
	Industry Canada ICES-003 Class A
Safety	Compliance to UL/CSA 60950-1, EN 60950-1 and IEC 60950-1 CB Scheme. Marked with U.S. NRTL, Canadian Safety and CE Mark.
RoHS/WEEE compliance	DIRECTIVE 2011/65/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 8 June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. (RoHS)
	DIRECTIVE 2002/96/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on waste electrical and electronic equipment (WEEE)

Ordering Information

Part Number	Description
AXP1440	ATCA SHELF - 14 SLOT, 19", 13U, 40G, PP SHMM
CENT-4440-R20-01	(1) AXP1440, (1) ATCA-F140 WITH FULL SOFTWARE PACKAGE
CENT-4440-R20-02	(1) AXP1440, (2) ATCA-F140 WITH FULL SOFTWARE PACKAGE
Optional Platform Products	
RTM-ATCA-F140	RTM for the ATCA-F140 with SFP/SFP+/QSFP sockets
PRAMC-7311	Mid-size AMC with Intel Core i7-2655LE processor, 2.2GHZ, 4GB DDR3
PRAMC-7311-16GB	Mid-size AMC with Intel Core i7-2655LE processor, 2.2GHZ, 16GB DDR3
SFP-CO-RJ-45	1G Small Form-factor Pluggable (SFP) - copper - RJ-45 connector
SFP-MM-SX-LC	1G Small Form-factor Pluggable (SFP) module - 850NM, SX, LC connector
SFPP-MM-SR-LC	10G Small Form-factor Pluggable Plus (SFPP) module - 850NM, SR, LC connector
SFPP-SM-LR-LC	10G Small Form-factor Pluggable Plus (SFPP) module - 1310NM, LR, LC connector
SFPP-MM-SR-LC-DR	10G Small Form-factor Pluggable Plus (SFPP) module - dual rate, 850NM, SR, LC connector
SFPP-CO-RJ-45-3M	10G Small Form-factor Pluggable Plus (SFPP) Direct Attached Copper (DAC) cable - 3 meters
CABLE-OPT-F102-5M	Optical cable for multi-mode, SFP and SFPP connections (5M)
QSFP-40G-SR4-MODULE	40G QSFP+ MODULE - 40GBASE-SR4 - 850NM - FOR MULTIMODE FIBER - MTP (MPO) CONNECTOR
CABLE-COP-QSFP-3M	40G QSFP+ Direct Attached Copper (DAC) cable - 3 meters
CABLE-OPT-QSFP-5M	Optical cable for multimode, QSFP+ connections, 2x MTP (MPO) connectors - 5 meters
CABLE-B-OPT-QSFP-5M	Optical break-out cable for multimode, 1x MTP (MPO) connector, 8x LC connectors - 5 meters
SFP-FILLER	EMI & dust plug for SFP and SFP+ receptacles
AXP-F-FILL-PANEL	Blank filler panel, AXP1620, AXP1440, AXP1410 – Front
AXP-R-FILL-PANEL	Blank filler panel, AXP1620, AXP1440, AXP1410 – Rear
ACC/CABLE/SER/DTE/6E	MicroDSUB-9 to DSUB-9 serial adapter cable for shelf manager front access ALREADY INCLUDED IN PLATFORM CORE PRODUCTS
CABLE/RJ45/DSUB/6E	RJ45 to DSUB-9 serial adapter and cable for shelf manager rear access
RJ45-DSUB-ATCA	RJ45 to DSUB-9 serial adapter cable for ATCA-F140 serial console

SOLUTION SERVICES

Artesyn Embedded Technologies provides a portfolio of solution services optimized to meet your needs throughout the product lifecycle. Design services help speed time-to-market. Deployment services include global 24x7 technical support. Renewal services enable product longevity and technology refresh.

WORLDWIDE OFFICES

United States	+1 888 412 7832	Japan	+81 3 5403 2730
Hong Kong	+852 2176 3540	Korea	+82 2 6004 3268
China	+86 400 8888 183		



www.artesyn.com

Artesyn Embedded Technologies, Artesyn, the Artesyn Embedded Technologies logo and Centellis are trademarks and service marks of Artesyn Embedded Technologies, Inc. Centellis® is registered in one or more countries. AdvancedTCA and ATCA are trademarks of PICMG. Intel and Xeon are trademarks of Intel Corporation or its subsidiaries in the United States and other countries. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners. Specifications are subject to change without notice. © 2018 Artesyn Embedded Technologies, Inc. All rights reserved. For full legal terms and conditions, please visit www.artesyn.com/legal.

AXP1440-Centellis4440-DS 07Feb2018