

CERTIFICATE

No. B 15 07 13890 02251



Product Service

Holder of Certificate: **Astec International Ltd.**
16th Floor, Lu Plaza, 2 Wing Yip Street
Kwun Tong
Kowloon
HONG KONG



Certification Mark:



Product: **Converter
(DC-DC Converter)**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 682301505401

Valid until: 2020-07-09

Date, 2015-07-13
Page 1 of 2


(Yager Bi)





CERTIFICATE
No. B 15 07 13890 02251

Model(s): **ADQ500-48S12XXXXXXXXXX**
(Where XXXXXXXXX may be represented by any ASCII character code, which have no affection to product safety)

Parameters:

Rated Input :	36-75VDC, 15A Max
Rated Output :	12VDC, 30A (without baseplate) or 40A (with baseplate)
Protection Class :	Built-in equipment, consider in end system
Degree of Protection :	IPX0
Remark :	<ul style="list-style-type: none">- When installing the equipment, all requirements of the mentioned standard must be fulfilled.- Refer to the installation and operating instruction from manufacturer for the details of loading condition and operating ambient temperature.- Clearance was evaluated for operating altitude up to 3000m above sea level.- Basic insulation is provided between input circuit and output circuit/baseplate.- The built-in converter shall be connected to a source which is insulated from the AC mains supply by double or reinforced insulation.- The output is energy hazardous (> 240VA), when installing into the end system, the output and its associated wires must not be touched.- Built-in type equipment, suitable enclosure should be provided by end system.- The built-in converter has no in-line fuse. For safe operation, an external 30A, 125VDC fast acting certified fuse must be employed as input line fuse before installation.

Tested according to: EN 60950-1:2006/A2:2013

Production Facility(ies): 26247, 41329

Page 2 of 2