



Product Service

CERTIFICATE


No. B 16 04 13890 02674

Holder of Certificate: **Astec International Ltd.**

16th Floor, Lu Plaza, 2 Wing Yip Street
Kwun Tong
Kowloon
HONG KONG



Certification Mark:



Product:

**Switching power supply unit
(Switching Power Supply)**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 682301603502

Valid until: 2021-04-27



Date, 2016-04-29
Page 1 of 2

(Yager Bi)



CERTIFICATE

No. B 16 04 13890 02674

Model(s): **CSU550AP-3-XXX**
 (Where "XXX" can be blank or any alphanumeric character, which is for marketing purpose only and have no impact on safety)

Parameters:

Rated Input :	100-240VAC, 50/60Hz, 7.2A-3.5A or 240VDC, 3.6A
Rated DC Output :	12.2V, 45A MAX.; 12.2VSB, 2.5A MAX. Total output power not to exceed 550W
Construction :	Built-in
Protection Class :	I
Degree of Protection :	IPX0
Remarks :	<ul style="list-style-type: none"> - When installing these equipments, all requirements of the mentioned standard must be fulfilled. - Clearance was evaluated for operating altitude up to 5000m above sea level. - These power supply contains output exceeding 240VA, when installing into end system, care must be taken that the output and associated wire(s) may not be touched. - Built-in type equipment, suitable enclosure should be provided in end system. - This equipment was evaluated for use in tropical conditions. - The maximum operating temperature is 50°C.

Tested according to: EN 60950-1:2006/A2:2013

Production Facility(ies): 41329