

Data Sheet

Total Power: 24 Watts
Input Voltage: 90 - 264 Vac
of Outputs: Single



SPECIAL FEATURES

- Universal AC input
- Fully regulated output
- EN61000-3-2 compliant
- Overcurrent and overvoltage protection
- High efficiency
- High MTBF
- IEC320 AC input receptacle 3 pin (type C14)
- Built-in EMI filter (CISPR 22 Class B)
- LED power good indicator
- AC input fuse
- Efficiency Level V
- Meets K.21 Basic Surge requirement

SAFETY

- UL 60950-1
- CSA-C22.2 No.60950
- TUV EN/IEC60950-1
- CE Mark: LVD, EMC & ErP 2011
- CCC Certificate
- CB Certificate

Electrical Specifications

Input	
Input range	90 - 264 Vac (wide range)
Frequency	47 - 63 Hz
Inrush current	50 A maximum @ 230 Vac, cold start 25 °C
Input current	1 A maximum
Efficiency	82% typical
EMI/RFI	FCC Part 15, Class B & EN55022 (CISPR 22) Class B
Safety ground leakage current	250 μ A maximum @ 50/60 Hz, 264 Vac input
Output	
Maximum Power (Po)	24 W
Hold-up time	20 ms. minimum at full load @ 115 Vac, 60 Hz
Overvoltage protection	28 V Latching type, recycle AC to reset
Overcurrent protection	Output short circuit protection auto recover Overload protection @ 2.5 - 5 A
Thermal protection	Latching type, recycle AC to reset
Cable/connector	DC cable with 2.5 mm I.D. / 5.5 mm O.D. center plug DC plug center +v DC plug outer -v

Environmental Specifications


Operating temperature	-5 °C to +50 °C ambient
Storage temperature	-45 °C to +85 °C
Electromagnetic susceptibility	Designed to meet EN61000-4-2, -4, -5, level 3; EN61000-4-3, -6, 6 v/m; EN61000-3-3 and EN61000-3-2 Class A
Humidity	Operating; non-condensing 5% to 90% RH
MTBF calculated	> 850,000 hours at full load and 25 °C ambient conditions Telcordia SR332 issue 1 (Method 1, Case 3)

Ordering Information

Model Number	Maximum Power	Output Voltage	Minimum Load	Maximum Load	Peak Load ¹	Regulation ²	Ripple P/P (PARD) ³
AD2412N3L	24 W	12 Vdc	0.1 A	2 A	2.4 A	± 5%	< 120 mV

1. Peak current lasting 200 ms every 3 seconds.
2. At 25 °C including initial tolerance, line voltage, load currents and output voltages adjusted to factory settings.
3. Peak-to-peak with 20 MHz bandwidth and 10µF (tantalum capacitor) in parallel with a 0.1µF capacitor at rated line voltage and load ranges.
4. Power supply will operate with no load.

Mechanical Drawing



Notes:

1. Specifications subject to change without notice.
2. All dimensions in inches (mm), tolerance is ± 0.02" (±0.5 mm)
3. Warranty: 2 years
4. Weight: 0.61 lb./ 0.28 kg
5. AC input power cord sold separately
6. Specifications at factory settings at 115 VAC input, 25 °C unless otherwise stated
7. AC Input Connector: IEC320, C-13

WORLDWIDE OFFICES

Americas

2900 S.Diablo Way
Tempe, AZ 85282
USA
+1 888 412 7832

Europe (UK)

Waterfront Business Park
Merry Hill, Dudley
West Midlands, DY5 1LX
United Kingdom
+44 (0) 1384 842 211

Asia (HK)

14/F, Lu Plaza
2 Wing Yip Street
Kwun Tong, Kowloon
Hong Kong
+852 2176 3333



www.artesyn.com

While every precaution has been taken to ensure accuracy and completeness in this literature, Artesyn Embedded Technologies assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions. Artesyn Embedded Technologies, Artesyn and the Artesyn Embedded Technologies logo are trademarks and service marks of Artesyn Embedded Technologies, Inc. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners.
© 2015 Artesyn Embedded Technologies, Inc.

For more information: www.artesyn.com/power
For support: productsupport.ep@artesyn.com