

## UL TEST REPORT AND PROCEDURE

<b>Standard:</b>	UL 60950-1, 2nd Edition, 2014-10-14 (Information Technology Equipment - Safety - Part 1: General Requirements) CAN/CSA C22.2 No. 60950-1-07, 2nd Edition, 2014-10 (Information Technology Equipment - Safety - Part 1: General Requirements)
<b>Certification Type:</b>	Component Recognition
<b>CCN:</b>	QQGQ2, QQGQ8 (Power Supplies for Information Technology Equipment Including Electrical Business Equipment)
<b>Product:</b>	Switching Power Supply
<b>Model:</b>	DS3000PE-3-XXX where -XXX can be any alphanumeric character, symbol or blank that represents customer identity that do not affect safety and DS3000PE-3-403
<b>Rating:</b>	For Model DS3000PE-3-XXX  Forward Airflow Condition:  AC Input: 16A max, 100-120V, 50/60Hz DC-outputs: 112.5A max +12V, 4.5A max +12Vsb, maximum output power is 1350W  AC Input: 16A max, 200-207V, 50/60Hz DC-outputs: 225.0A max +12V, 4.5A max +12Vsb, maximum output power is 2700W  AC Input: 16A max, 208-214V, 50/60Hz DC-outputs: 245.0A max +12V, 4.5A max +12Vsb, maximum output power is 2940W  AC Input: 16A max, 215-240V, 50/60Hz DC-outputs: 250.0A max +12V, 4.5A max +12Vsb, maximum output power is 3000W  Reverse Airflow Condition:  AC Input: 16A max, 100-120V, 50/60Hz DC-outputs: 112.5A max +12V, 4.5A max +12Vsb, maximum output power is 1350W  AC Input: 16A max, 200-207V, 50/60Hz DC-outputs: 231.7A max +12V, 4.5A max +12Vsb, maximum output power is 2730W  AC Input: 16A max, 208-214V, 50/60Hz DC-outputs: 231.70A max +12V, 4.5A max +12Vsb, maximum output power is 2730W  AC Input: 16A max, 215-240V, 50/60Hz DC-outputs: 231.7A max +12V, 4.5A max +12Vsb, maximum output power is 2730W  For Model DS3000PE-3-403:

AC Input: 16A max, 100-120V, 50/60Hz  
DC-outputs: 110.0A max +12.25V, 4.5A max +12Vsb, maximum  
output power is 1350W

AC Input: 16A max, 200-207V, 50/60Hz  
DC-outputs: 220.5A max +12.25V, 4.5A max +12Vsb, maximum  
output power is 2700W

AC Input: 16A max, 208-214V, 50/60Hz  
DC-outputs: 240.0A max +12.25V, 4.5A max +12Vsb, maximum  
output power is 2940W

AC Input: 16A max, 215-240V, 50/60Hz  
DC-outputs: 245.0A max +12.25V, 4.5A max +12Vsb, maximum  
output power is 3000W

**Applicant Name and Address:**

ASTEC INTERNATIONAL LIMITED  
16TH FL  
LU PLAZA  
2 WING YIP STREET  
KWUN TONG, KOWLOON HONG KONG

This is to certify that representative samples of the products covered by this Test Report have been investigated in accordance with the above referenced Standards. The products have been found to comply with the requirements covering the category and the products are judged to be eligible for Follow-Up Service under the indicated Test Procedure. The manufacturer is authorized to use the UL Mark on such products which comply with this Test Report and any other applicable requirements of UL LLC ('UL') in accordance with the Follow-Up Service Agreement. Only those products which properly bear the UL Mark are considered as being covered by UL's Follow-Up Service under the indicated Test Procedure.

The applicant is authorized to reproduce the referenced Test Report provided it is reproduced in its entirety.

UL authorizes the applicant to reproduce the latest pages of the referenced Test Report consisting of the first page of the Specific Technical Criteria through to the end of the Conditions of Acceptability.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL.

Prepared by: Jeffery Chan/Project Handler

Reviewed by: Brian Wong/Reviewer

### **Supporting Documentation**

The following documents located at the beginning of this Procedure supplement the requirements of this Test Report:

- A. Authorization - The Authorization page may include additional Factory Identification Code markings.
- B. Generic Inspection Instructions -
  - i. Part AC details important information which may be applicable to products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of this Test Report.
  - ii. Part AE details any requirements which may be applicable to all products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of each Test Report.
  - iii. Part AF details the requirements for the UL Certification Mark which is not controlled by the technical standard used to investigate these products. Products are permitted to bear only the Certification Mark(s) corresponding to the countries for which it is certified, as indicated in each Test Report.

### Product Description

The equipment is switching power supply, intended for building in as a component used in information technology equipment which employs with isolating transformers. Reinforced insulation is provided between primary and secondary. Basic insulation is provided between primary and PE (Protective Earth)

### Model Differences

Model DS3000PE-3-XXX is identical to model DS3000PE-3-403 except for the main output voltage. Main output voltage changed was done through firmware only. DS3000PE-3-403 has no reverse airflow condition.

### Technical Considerations

- Equipment mobility : for building-in
- Connection to the mains : pluggable A when non-detachable input cord in end system
- Operating condition : continuous
- Access location : operator accessible
- Over voltage category (OVC) : OVC II
- Mains supply tolerance (%) or absolute mains supply values : +10%, -10%
- Tested for IT power systems : No
- IT testing, phase-phase voltage (V) : N/A
- Class of equipment : Class I (earthed)
- Considered current rating of protective device as part of the building installation (A) : 30A
- Pollution degree (PD) : PD 2
- IP protection class : IP X0
- Altitude of operation (m) : 3048
- Altitude of test laboratory (m) : less than 2000 meters
- Mass of equipment (kg) : <18
- The product was submitted and evaluated for use at the maximum ambient temperature (T<sub>ma</sub>) permitted by the manufacturer's specification of: 40°C at full load. Output is reduced by 2.5% per °C from 40°C to 50°C
- The means of connection to the mains supply is: Pluggable A when non-detachable input cord in end system.,
- The product is intended for use on the following power systems: TN
- The equipment disconnect device is considered to be: Appliance inlet
- The class of laser product is: Class 1 (I) for indicating LED only, ,
- The product was investigated to the following additional standards: EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011+A2:2013 ,
- Fan forward airflow direction is blowing from Output to Input while reverse airflow direction is blowing from Input to Output side of power supply. DS3000PE-3-403 fan airflow direction is blowing from Output to Input side of power supply.

### Engineering Conditions of Acceptability

For use only in or with complete equipment where the acceptability of the combination is determined by UL LLC. When installed in an end-product, consideration must be given to the following:

- The following Production-Line tests are conducted for this product: Electric Strength, Earthing Continuity

- The end-product Electric Strength Test is to be based upon a maximum working voltage of: Primary-SELV: 335.3 Vrms, 707 Vpk, Primary-Earthed Dead Metal: 334.4 Vrms, 707 Vpk,
- The following secondary output circuits are SELV: +12V, +12Vsb, +12.25V (for DS3000PE-3-403 only),
- The following secondary output circuits are at hazardous energy levels: +12V, +12.25V (for DS3000PE-3-403 only),
- The following secondary output circuits are at non-hazardous energy levels: +12Vsb,
- The power supply terminals and/or connectors are: Not investigated for field wiring except AC inlet,
- The maximum investigated branch circuit rating is: 30 A
- The investigated Pollution Degree is: 2
- Proper bonding to the end-product main protective earthing termination is: Required
- An investigation of the protective bonding terminals has: Been conducted
- The following magnetic devices (e.g. transformers or inductor) are provided with an OBJY2 insulation system with the indicated rating greater than Class A (105°C): T202, T801, T802 (Class F) and T601 (Class A),
- The following end-product enclosures are required: Fire, Electrical
- The equipment is suitable for direct connection to: AC mains supply
- Fan is not accessible by user when power supply is inserted in end system. And since this power supply is component type, fan blade symbol is affixed on the unit. Compliance of section 4.4.5 of UL60950-1 to be determined in end system.