



Product Service

CERTIFICATE

No. B 14 11 13890 02140

Holder of Certificate: **Astec International Ltd.**

16th Floor, Lu Plaza, 2 Wing Yip Street
Kwun Tong
Kowloon
HONG KONG



Certification Mark:



Product: **Power supply
(Switching Power Supply)**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 68230915709

Valid until: 2019-11-15



Date, 2014-11-17
Page 1 of 3

(Signature)
(Yager Bi)

**CERTIFICATE**

No. B 14 11 13890 02140

Model(s): DS760SL-3-403, DS760SL-3, DS760SL-3-001, DS760SL-3-002, DS760SL-3-003, 7001497-xxxx OR A237
(Where xxxx is blank or any alphanumeric characters representing the customer identification)

Parameters:

Rated Input :	For model 7001497-xxxx OR A237, DS760SL-3-002, DS760SL-3: 100-120VAC/200-240VAC, 8.8A max., 50/60Hz; For model DS760SL-3-001, DS760SL-3-003: 100-120VAC/200-240VAC, 6.8A max., 50/60Hz; For model DS760SL-3-403: 100-120VAC/200-240VAC, 7.8A max., 50/60Hz
Rated Output :	See page 3 for details
Construction :	Built-in
Protection Class :	I
Degree of Protection :	IPX0
Remarks :	<ul style="list-style-type: none"> - Clearance was evaluated for operating altitude up to 4000m above sea level. - When installed in end product, suitable enclosure should be provided and all requirement of relevant standard should be fulfilled. - Refer to the installation and operating instruction from manufacturer for the details of loading condition and operating temperature. - This power supply contains output exceeding 240VA, when installing into end system, care must be taken that the output and associated wire(s) may not be touched.

Tested according to: EN 60950-1/A2:2013

Production Facility(ies): 26247, 62777, 28532, 41329

Page 2 of 3

CERTIFICATE
No. B 14 11 13890 02140



Product Service

Model	Input	DC output
7001497-xxxx OR A237 DS760SL-3-002	100-120VAC/200-240VAC, 8.8A max., 50/60Hz	V1 12.0V, 62.3A max.; Vsb 3.35V, 3.6A max.; Total power 760W
DS760SL-3	100-120VAC/200-240VAC, 8.8A max., 50/60Hz	V1 12.0V, 62.3A max.; Vsb 5.0V, 2.4A max.; Total power 760W
DS760SL-3-001	100-120VAC/200-240VAC, 6.8A max., 50/60Hz	V1 12.0V, 49.0A max.; Vsb 5.0V, 2.4A max.; Total power 600W
DS760SL-3-003	100-120VAC/200-240VAC, 6.8A max., 50/60Hz	V1 12.0V, 49.0A max.; Vsb 3.35V, 3.6A max.; Total power 600W
DS760SL-3-403	100-120VAC/200-240VAC, 7.8A max., 50/60Hz	V1 12.0V, 54.83A max.; Vsb 5.0V, 2.4A max.; Total power 670W