


Product	Power Supply, Building-in Type
Applicant	Astec International Ltd. 16th Floor, Lu Plaza, 2 Wing Yip Street, Kwun Tong, Kowloon, Hong Kong
Manufacturer	Astec International Ltd. 16th Floor, Lu Plaza, 2 Wing Yip Street, Kwun Tong, Kowloon, Hong Kong
Factory	(2) See page 2
Ratings	4.2/2.2A 100-127/200-250V 50/60Hz or 1.6A 220-300V DC
Trade mark	
Model / Type Ref.	LPS152
Principal characteristics	Cl. I. DC-outputs: Convection cooling 22A max. +5V. Forced air cooling 30A max. +5V. Maximum continuous output power is: - 75W with cover and convection cooling, -110W without cover and convection cooling, -130W with cover with 30CFM forced air cooling, - 150W without cover with 30CFM forced air cooling
A sample of the product was tested and found to be in conformity with	OFF EN 60950-1:2006;A11;A1;A12;A2
Validity	This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.
Additional information	Compliance with requirements regarding building-in, protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.
Additional model(s)	(2) See page 2

Date of issue 14-01-2016



Nastaran Vadoodi

Certification Department

Nemko AS

Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway

TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com

ENTERPRISE NUMBER NO974404532

Additional model(s)

Product Power Supply, Building-in Type
Pos. No 1
Model / Type Ref. LPS153
Trade mark (if different from page 1)
Rating 4.2/2.2A 100-127/200-250V 50/60Hz or 1.6A 220-300V DC
Principal characteristics Cl. I. DC-outputs: Convection cooling 9.1A max. +12-15V. Forced air cooling 12.5A max. +12-15V. Maximum continuous output power is: - 75W with cover and convection cooling, -110W without cover and convection cooling, -130W with cover with 30CFM forced air cooling - 150W without cover with 30CFM forced air cooling

Product Power Supply, Building-in Type
Pos. No 2
Model / Type Ref. LPS155
Trade mark (if different from page 1)
Rating 4.2/2.2A 100-127/200-250V 50/60Hz or 1.6A 220-300V DC
Principal characteristics Cl. I. DC-outputs: Convection cooling 4.5A max. +24-28V. Forced air cooling 6.2A max. +24-28V. Maximum continuous output power is: - 75W with cover and convection cooling, -110W without cover and convection cooling, -130W with cover with 30 30CFM forced air cooling,
- 150W without cover with 30CFM forced air cooling

Factories

Astec Power Philippines Inc.
Main Avenue Corner Road "J" Cavite Export Processing
Zone Rosario, Cavite, 4106
Philippines

Astec Power Philippines Inc.
104 Laguna Blvd., Laguna Technopark, Sta. Rosa
Laguna, 4026
Philippines

Date of issue 14-01-2016



Nastaran Vadoodi

Certification Department

Nemko AS

Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com
ENTERPRISE NUMBER NO974404532