


Product	Power Supply, Building-in Type
Applicant	Astec International Ltd. 16th Floor, Lu Plaza, 2 Wing Yip Street, Kwun Tong, Kowloon, Hong Kong
Manufacturer	Astec International Ltd. 16th Floor, Lu Plaza, 2 Wing Yip Street, Kwun Tong, Kowloon, Hong Kong
Factory	(2) See page 2
Ratings	4.5A 100-250V 50/60/440Hz or 3.4A 120-300V DC
Trade mark	
Model / Type Ref.	LPS252
Principal characteristics	Cl. I. DC-output (30CFM forced air cooling): +3-6V, max. 50A, max. 250W (with cover). +3-6V, max. 40A, max. 200W (without cover)
A sample of the product was tested and found to be in conformity with	OFF EN 60950-1:2006;A11;A1;A12;A2
Validity	This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.
Additional information	Compliance with requirements regarding building-in, protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.
Additional model(s)	(3) See page 2

Date of issue 14-01-2016



Nastaran Vadoodi

Certification Department

Nemko AS

Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com
ENTERPRISE NUMBER NO974404532

Additional model(s)

Product Power Supply, Building-in Type
Pos. No 1
Model / Type Ref. LPS253
Trade mark (if different from page 1)
Rating 4.5A 100-250V 50/60/440Hz or 3.4A 120-300V DC
Principal characteristics Cl. I. DC-output (30CFM forced air cooling): +6-12V, max. 21A, max. 250W (with cover). +6-12V, max. 16.6A, max. 200W (without cover)

Product Power Supply, Building-in Type
Pos. No 2
Model / Type Ref. LPS254
Trade mark (if different from page 1)
Rating 4.5A 100-250V 50/60/440Hz or 3.4A 120-300V DC
Principal characteristics Cl. I. DC-output (30CFM forced air cooling): +12-24V, max. 16.6A, max. 250W (with cover). +12-24V, max. 13-3A, max. 200W (without cover)

Product Power Supply, Building-in Type
Pos. No 3
Model / Type Ref. LPS255
Trade mark (if different from page 1)
Rating 4.5A 100-250V 50/60/440Hz or 3.4A 120-300V DC
Principal characteristics Cl. I. DC-output (30CFM forced air cooling): +24-28V, max. 10.4A, max. 250W (with cover). +24-28V, max. 8.3A, max. 200W (without cover)

Factories

Astec Power Philippines Inc.
Main Avenue Corner Road "J" Cavite Export Processing
Zone Rosario, Cavite, 4106
Philippines

Astec Power Philippines Inc.
104 Laguna Blvd., Laguna Technopark, Sta. Rosa
Laguna, 4026
Philippines

Date of issue 14-01-2016



Nastaran Vadoodi
Certification Department

Nemko AS
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com
ENTERPRISE NUMBER NO974404532