

Product	Power Supply, Open frame Building-in Type
Applicant	Astec International Ltd. 16th Floor, Lu Plaza, 2 Wing Yip Street Kwun Tong, Kowloon Hong Kong
Manufacturer	Astec International Ltd. 16th Floor, Lu Plaza, 2 Wing Yip Street Kwun Tong, Kowloon Hong Kong
Factory	(4) See page 2
Ratings	1.2A 100-250V 50/60/440Hz or 0.8A 120-300VDC
Trade mark	
Model / Type Ref.	LPS22
Principal characteristics	Cl. I, DC-output: 8A +5V. Maximum Continuous Output Power is 25W convection cooling. Maximum Continuous Output Power is 40W with 30CFM forced air
A sample of the product was tested and found to be in conformity with	OFF EN 60950-1:2006;A11;A1;A12;A2
Replaces	This certificate replaces previous certificate No. P15220585, due to change altitude of operation and removed Vishay from Optocouplers list and minor revision on PCB to increase creepage distance and clearance.
Validity	This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.
Additional information	Compliance with requirements regarding building-in, protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.
Additional model(s)	(3) See page 2

Date of issue 07-07-2017

Jiyea Gim

Jiyea Gim
Certification Department

Nemko AS
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com
ENTERPRISE NUMBER NO974404532

Additional model(s)

Product	Power Supply, Open frame Building-in Type
Pos. No	1
Model / Type Ref.	LPS23
Trade mark (if different from page 1)	
Rating	1.2A 100-250V 50/60/440Hz or 0.8A 120-300VDC
Principal characteristics	Cl. I, DC-output: 3.4A +12V. Maximum Continuous Output Power is 25W convection cooling. Maximum Continuous Output Power is 40W with 30CFM forced air
Product	Power Supply, Open frame Building-in Type
Pos. No	2
Model / Type Ref.	LPS24
Trade mark (if different from page 1)	
Rating	1.2A 100-250V 50/60/440Hz or 0.8A 120-300VDC
Principal characteristics	Cl. I, DC-output: 2.7A +15V. Maximum Continuous Output Power is 25W convection cooling. Maximum Continuous Output Power is 40W with 30CFM forced air
Product	Power Supply, Open frame Building-in Type
Pos. No	3
Model / Type Ref.	LPS25
Trade mark (if different from page 1)	
Rating	1.2A 100-250V 50/60/440Hz or 0.8A 120-300VDC
Principal characteristics	Cl. I, DC-output: 1.8A +24V. Maximum Continuous Output Power is 25W convection cooling. Maximum Continuous Output Power is 40W with 30CFM forced air

Factories

Astec Power Philippines Inc.
Main Avenue Corner Road "J", Cavite Export Processing
Zone, Rosario, Cavite
Philippines

Astec Electronics (Luoding) Co., Ltd.
No. 68, Baocheng Road East, Fucheng, Luoding,
Guangdong
China

Astec Power Philippines Inc.
104 Laguna Blvd., Laguna Technopark, Sta. Rosa
Laguna, 4026
Philippines

Zhongshan General Carton Box Factory Co., Ltd.
No. 62, Qi Guan Rd. West, Shiqi District, Zhongshan
City, Guangdong, 528400
China

Date of issue 07-07-2017



Jiyea Gim

Certification Department

Nemko AS

Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com
ENTERPRISE NUMBER NO974404532