

Product	Switching Power Supply for building in
Applicant	Astec International Ltd.,Philippine Branch 3rd and 4th Floor Techno Plaza One Bldg., #18 Orchard Road, Eastwood City Cyberpark, Bagumbayan Quezon City 1110 Philippines
Manufacturer	Astec International Ltd.,Philippine Branch 3rd and 4th Floor Techno Plaza One Bldg., #18 Orchard Road, Eastwood City Cyberpark, Bagumbayan Quezon City 1110 Philippines
Factory	Astec Power Philippines Inc. Main Avenue corner Road "J" Cavite Export Processing Zone Rosario, Cavite 4106 Philippines <input type="checkbox"/> See next page(s)
Ratings	5.4A 100-250V 50/60Hz
Trade mark	  OR EMBEDDED TECHNOLOGIES
Model / Type Ref.	NTS353-(CEF)
Principal characteristics	CI.I, DC-outputs: 29.17A ±12V, 2A +5VSTBY, 1A +12V(FAN_OUT) Maximum continuous output power 350W. Derate each output 2.5% per degree from 50°C to 70°C ambient temperature. <input type="checkbox"/> See next page(s)
A sample of the product was tested and found to be in conformity with	OFF                      EN 60950-1:2006;A11;A1;A12;A2
Validity	This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.
Additional information	<input type="checkbox"/> See next page(s)  The abovementioned certified equipment complies with current regulatory requirements regarding electrical safety in Norway and other EU/EEA member states, as far as this can be checked. Compliance with requirements regarding building-in, protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.
Additional model(s)	<input checked="" type="checkbox"/> See next page(s)

Date of issue 03-09-2015

*Nastaran Vadoodi*

Nastaran Vadoodi

Certification Department

**Nemko AS**

Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway

TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com

ENTERPRISE NUMBER NO974404532

Product Switching Power Supply for building in  
Pos. No 1  
Model / Type Ref. NTS355-(CEF)  
Trade mark (if different from page 1)  
Rating 5.4A 100-250V 50/60Hz  
Principal characteristics Cl.I, DC-outputs: 14.58A max  $\pm 24V$ , 2Amax +5VSTBY, 1Amax +12V(FAN\_OUT) Maximum continuous output power 350W. Derate each output 2.5% per degree from 50°C to 70°C ambient temperature.

Product Switching Power Supply for building in  
Pos. No 2  
Model / Type Ref. NTS358-(CEF)  
Trade mark (if different from page 1)  
Rating 5.4A 100-250V 50/60Hz  
Principal characteristics Cl.I, DC-outputs: 7.29A max  $\pm 48V$ , 2Amax +5VSTBY, 1Amax +12V(FAN\_OUT) Maximum continuous output power 350W. Derate each output 2.5% per degree from 50°C to 70°C ambient temperature.

Product Switching Power Supply for building in  
Pos. No 3  
Model / Type Ref. NTS359-(CEF)  
Trade mark (if different from page 1)  
Rating 5.4A 100-250V 50/60Hz  
Principal characteristics Cl.I, DC-outputs: 6.43A max  $\pm 54.4V$ , 2Amax +5VSTBY, 1Amax +12V(FAN\_OUT) Maximum continuous output power 350W. Derate each output 2.5% per degree from 50°C to 70°C ambient temperature.

Date of issue 03-09-2015



Nastaran Vadoodi

Certification Department

**Nemko AS**

Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532