

CB TEST CERTIFICATE CERTIFICAT D'ESSAI OCProduct
ProduitName and address of the applicant
Nom et adresse du demandeurName and address of the manufacturer
Nom et adresse du fabricantName and address of the factory
Nom et adresse de l'usineNote: When more than one factory, please report on page 2
Note: Lorsque il y plus d'une usine, veuillez utiliser la deuxième pageRatings and principal characteristics
Valeurs nominales et caractéristiques principalesTrademark (if any)
Marque de fabrique (si elle existe)Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeurModel / Type Ref.
Ref. De typeAdditional information (if necessary may also be reported on page 2)
Les informations complémentaires (si nécessaire, peuvent être indiqués sur la deuxième pageA sample of the product was tested and found to be in conformity with
Un échantillon de ce produit a été essayé et a été considéré conforme à la
As shown in the Test Report Ref. No. which forms part of this Certificate
Comme indiqué dans le Rapport de tests numéro de référence qui constitue partie de ce CertificatThis CB Test Certificate is issued by the National Certification Body
Ce Certificat de test OC est établi par l'Organisme National de Certification

Power Supply, Open frame Building-in Type

Astec International Ltd., Philippine Branch
3rd & 4th Floor Techno Plaza One Bldg. #18 Orchard Road, Eastwood City Cyberpark, Bagumbayan, Quezon City 1110
PhilippinesAstec International Ltd., Philippine Branch
3rd & 4th Floor Techno Plaza One Bldg. #18 Orchard Road, Eastwood City Cyberpark, Bagumbayan, Quezon City 1110
Philippines Additional information on page 2

AC Input: 4A 100-250V 50/60Hz; DC Input: 4A 120Vmin – 300Vmax. CI.I, DC-outputs: 180W: 12A +12V to +24V, 2A +5VSTBY, 1A +12V (FAN_OUT); 110W: 7.3A +12V to +24V, 1A +5VSTBY, 0.5A +12V (FAN_OUT); 75W: 5.33A +12V to +24V, 1A +5VSTBY, 0.5A +12V (FAN_OUT).



LPS174

Maximum continuous output power of: - 180W with or without cover at 30CFM forced-air cooling, 110W without cover at natural convection cooling, 75W with cover at natural convection cooling, Each output have a derating of 2.5% per degree from 50°C to 70°C ambient temperature.

 Additional information on page 2

IEC 60950-1(ed.2);am1;am2

294923

Astec Power Philippines Inc.
Main Avenue Corner Road "J" Cavite Export Processing
Zone Rosario, Cavite 4106
Philippines

Astec Electronics (Luoding) Co., Ltd.
No. 68, Baocheng Road East, Fucheng, Luoding,
Guangdong, 527200
China

Astec Power Philippines Inc.
104 Laguna Blvd., Laguna Technopark, Sta. Rosa
Laguna 4026
Philippines

Zhongshan General Carton Box Factory Co., Ltd.
No. 62 Qi Guan Road West, Shiqi District, Zhongshan
City, Guangdong, 528400
China